

## Nokian Hakka Truck

### Nokian Hakka Truck 861

Sizes  
 295/80 R 22.5  
 315/70 R 22.5  
 315/80 R 22.5  
 385/65 R 22.5

Application  
 All-season steer axle tyre
 

- Medium and long distance haul
- Buses and trucks



#### Maximum load capacities per axle

Size	LI/SS	Inflation Pressure	Single Load	Dual Load
295/80R22.5	152/148M	8,50 bar	7100 kg @130 km/h	12600 kg @ 130 km/h
315/70R22.5	152/148M	8,50 bar	7100 kg @ 130 km/h	12600 kg @ 130 km/h
	154/150L	9,00 bar	7500 kg @ 120 km/h	13400 kg @ 120 km/h
315/80R22.5	154/150M	8,25 bar	7500 kg @130 km/h	13400 kg @ 130 km/h
	156/150L	8,50 bar	8000 kg @120 km/h	13400 kg @ 120 km/h
385/65R22.5	158L	8,50 bar	8500 kg @120 km/h	-
	160K	9,00 bar	9000 kg @110 km/h	-

#### Tyre dimensions

Tyre Size	Tread depth (mm)	Approved Rims (in)	Overall Diameter (mm)	Tyre Width (mm)	Static Loaded Radius (mm)	Rolling Circ. (mm)	Minimum Dual Spacing (mm)
295/80R22.5	15,5	<b>9.00</b> , 8.25	1050	300	488	3185	335
315/70R22.5	15,0	<b>9.00</b> , <b>8.25</b>	1025	314	472	3109	335
315/80R22.5	15,5	<b>9.00</b> , 9.75	1079	313	502	3281	351
385/65R22.5	15,0	<b>11.75</b> , 12.25	1084	377	501	3293	-

Compound  
 Special compound for All-season use

#### Properties

- Wide zig-zag shaped grooves provide good grip
- Low tyre noise and low rolling resistance
- DSI (Driving Safety Indicator)
- SPIRAL SIPE SYSTEM
- M+S marking

#### Certificates

- E9 00 2045 (295/80 R 22.5)
- E9 00 2056 (315/70 R 22.5)
- E9 00 2053 (315/80 R 22.5)
- E9 00 2044 (385/65 R 22.5)
- E4-0017668-s (Noise homologation)

30.3.2011