

Nokian Hakkapeliitta Truck

Nokian Hakkapeliitta Truck D

Sizes
 315/80 R 22.5
 315/70 R 22.5
 295/80 R 22.5

Application
 Special winter traction tyre

- Autumn fitting
- Long distance haul
- Long distance busses



Technical information

Maximum load capacities per axle

Size	Pattern	LI/SS	Inflation Pressure	Single Load Capacity	Dual Load Capacity
315/80R22.5	Truck D	154/150M	8,25 bar	7500 kg @ 130 km/h	13400 kg @ 130 km/h
		156/150L	8,50 bar	8000 kg @ 120 km/h	-
315/70R22.5	Truck D	152/148M	8,50 bar	7100 kg @ 130 km/h	12600 kg @ 130 km/h
		154/150L	9,00 bar	7500 kg @ 120 km/h	13400 kg @ 120 km/h
295/80R22.5	Truck D	152/148M	8,50 bar	7100 kg @ 130 km/h	12600 kg @ 130 km/h

Tyre dimensions

Tyre Size	Pattern Design	Tread depth (mm)	Approved Rims (in)	Overall Diameter (mm)	Tyre Width (mm)	Static Loaded Radius (mm)	Rolling Circ. (mm)	Minimum Dual Spacing (mm)
315/80R22.5	Truck D	20,0	9.00, 9.75	1087	312	504	3304	351
315/70R22.5	Truck D	19,5	9.00, 9.75	1032	314	476	3137	351
295/80R22.5	Truck D	20,0	9.00, 8.25	1063	296	495	3231	335

Compound
 Special compound for winter drive axle use

Properties
 Best grip on packed snow and ice, main roads

- Low rolling resistance
- Low tyre noise
- Excellent durability
- 3D-siping
- Patented Twin Block pattern
- Over 1000 transverse sipes
- Sipe activators
- DSI (Driving Safety Indicator)
- WSI (Winter Safety Indicator)

18.06.2014