

Nokian Hakkapeliitta Truck

Nokian Hakkapeliitta Truck E

Sizes 295/80 R 22.5
315/70 R 22.5
315/80 R 22.5

Application Extreme-Class winter drive axle tyre

- For all kind of winter conditions on trucks and buses



Maximum load capacities per axle

Size	Pattern	LI/SS	Inflation Pressure	Single Load	Dual Load
295/80R22.5	Truck E	152/148M	8,50 bar	7100 kg @130 km/h	12600 kg @ 130 km/h
315/70R22.5	Truck E	152/148M 154/150L	8,50 bar 9,00 bar	7100 kg @ 130 km/h 7500 kg @ 120 km/h	12600 kg @ 130 km/h 13400 kg @ 120 km/h
315/80R22.5	Truck E	154/150M 156/150L	8,25 bar 8,25 bar 8,50 bar	7500 kg @130 km/h - 8000 kg @120 km/h	13400 kg @130 km/h 13400 kg @120 km/h -

Tyre dimensions

Tyre Size	Pattern Design	Tread depth (mm)	Approved Rims (in)	Overall Diameter (mm)	Tyre Width (mm)	Static Loaded Radius (mm)	Rolling Circ. (mm)	Minimum Dual Spacing (mm)
295/80R22.5	Truck E	20,0	9.00, 8.25	1064	296	495	3231	335
315/70R22.5	Truck E	20,0	9.00, 8.25	1031	314	476	3136	351
315/80R22.5	Truck E	20,0	9.00, 9.75	1086	312	503	3292	351

Compound Special compound for winter drive axle use

Properties

- Best possible grip due to aggressive grooving and siping
- Good self-cleaning even on deep snow and slush
- Marked stud arrangement in 6 rows
- DSI - Driving Safety Indicator
- WSI - Winter Safety Indicator

Certificates

- E9 00 2045 (295/80 R 22.5)
- E9 00 2056 (315/70 R 22.5)
- E9 00 2053 (315/80 R 22.5)
- E4-0019341-s (Noise homologation)

29.11.2011