

## Nokian NTR

### Nokian NTR 32 in 17.5" size

Sizes 215/75 R 17.5  
235/75 R 17.5

Application All-season steer axle tyre

- For delivery trucks
- Also for city buses



#### Maximum load capacities per axle

Size	Pattern Design	LI/SS	Inflation Pressure	Single Load	Dual Load
215/75R17.5	NTR 32	126/124M	7,00 bar	3400 kg @ 130 km/h	6400 kg @ 130 km/h
235/75R17.5	NTR 32	132/130M	7,75 bar	4000 kg @ 130 km/h	7600 kg @ 130 km/h

#### Tyre dimensions

Size	Pattern Design	Tread depth (mm)	Approved Rims (in)	Overall Diameter (mm)	Tyre Width (mm)	Static Loaded Radius (mm)	Rolling Circ. (mm)	Minimum Dual Spacing (mm)
215/75R17.5	NTR 32	12,5	<b>6.00</b> , 6.75	780	211	364	2386	239
235/75R17.5	NTR 32	12,5	<b>6.75</b> , 7.50	796	234	371	2440	262

Compound Special compound for All-season use

#### Properties

- Wide zig-zag shaped grooves provide good grip
- Low tyre noise and low rolling resistance
- Even tyre wear
- Robust 4-rib pattern with good stability and handling properties
- Stone ejectors
- M+S marking
- Driving Safety Indicators (DSI)

#### Certificates

- E4-54R-0022467 (215/75R17.5)
- E4-54R-0022468 (235/75R17.5)
- E4-117R-010435-S (Noise homologation)

07.07.2010