

Nokian NTR

Nokian NTR 32

Sizes
 275/70 R 22.5
 295/80 R 22.5
 315/70 R 22.5
 315/80 R 22.5

Application
 All-season steer axle tyre

- Medium and long distance haul
- Buses and trucks



Maximum load capacities per axle

Size	Pattern Design	LI/SS	Inflation Pressure	Single Load	Dual Load
275/70R22.5	NTR 32	148/145M	9,00 bar	6300 kg @ 130 km/h	11600 kg @ 130 km/h
295/80R22.5	NTR 32	152/148M	8,50 bar	7100 kg @ 130 km/h	12600 kg @ 130 km/h
315/70R22.5	NTR 32	154/150L	9,00 bar	7500 kg @ 120 km/h	13400 kg @ 120 km/h
		152/148M	8,50 bar	7100 kg @ 130 km/h	12600 kg @ 130 km/h
315/80R22.5	NTR 32	154/150M	8,25 bar	7500 kg @ 130 km/h	13400 kg @ 130 km/h
		156/150L	8,50 bar	8000 kg @ 120 km/h	
			8,25 bar		13400 kg @ 120 km/h

Tyre dimensions

Size	Pattern Design	Tread depth (mm)	Approved Rims (in)	Overall Diameter (mm)	Tyre Width (mm)	Static Loaded Radius (mm)	Rolling Circ. (mm)	Minimum Dual Spacing (mm)
275/70R22.5	NTR 32	14,5	8.25 , 7.50	957	277	444	2939	311
295/80R22.5	NTR 32	15,5	9.00 , 8.25	1040	298	482	3165	335
315/70R22.5	NTR 32	15,5	9.00 , 9.75	1015	310	470	3113	351
315/80R22.5	NTR 32	15,5	9.00 , 9.75	1072	310	495	3261	351

Compound
 Special compound for All-season use

Properties

- Wide zig-zag shaped grooves provide good grip
- Low tyre noise and low rolling resistance
- Even tyre wear
- Specially reinforced sidewalls (in size 275/70 R 22.5) protect the tyre from chafing against paving stones
- M+S marking
- Driving Safety Indicators (DSI)

Certificates

- E4-54R-0016899 (275/70 R 22.5)
- E4-54R-0016901 (295/80 R 22.5)
- E4-54R-0016902 (315/70 R 22.5)
- E4-54R-0016903 (315/80 R 22.5)
- E4-117R-010435-S (Noise homologation)

2.9.2008