

Nokian NTR

Nokian NTR 72 S

Sizes 385/65R22.5
385/55R22.5

Application All-season trailer tyre

- Also for steer axle use on main roads



Maximum load capacities per axle

| Size | Pattern Design | LI/SS | Inflation Pressure | Single Load | Dual Load |
|-------------|----------------|-------|--------------------|-------------------|-----------|
| 385/65R22.5 | NTR 72 S | 158L | 8,50 bar | 8500 kg @120 km/h | - |
| | | 160K | 9,00 bar | 9000 kg @110 km/h | - |
| 385/55R22.5 | NTR 72 S | 160K | 9,00 bar | 9000 kg @110 km/h | - |
| | | 158L | 8,50 bar | 8500 kg @120 km/h | - |

Tyre dimensions

| Size | Pattern Design | Tread depth (mm) | Approved Rims (in) | Overall Diameter (mm) | Tyre Width (mm) | Static Loaded Radius (mm) | Rolling Circ. (mm) | Minimum Dual Spacing (mm) |
|-------------|----------------|------------------|------------------------|-----------------------|-----------------|---------------------------|--------------------|---------------------------|
| 385/65R22.5 | NTR 72 S | 15,0 | 11.75, 12.25 | 1068 | 386 | 492 | 3277 | - |
| 385/55R22.5 | NTR 72 S | 15,0 | 11.75, 12.25 | 1001 | 381 | 464 | - | - |

Compound Special compound for All-season use

Properties

- Wide zig-zag shaped grooves provide good grip
- Even tyre wear
- M+S marking
- Driving Safety Indicators (DSI)

Certificates

- E4-54R-0016904 (385/65R22.5)
- E4-54R-0020041 (385/55R22.5)
- E4-117R-010438-S (Noise homologation)

17.6.2009