

29.5-29 40 MINE KING L-5S TL

For extreme underground loading application

PRODUCT CODE T445547

TIRE CLASSIFICATION CODE L-5S

APPLICATION Underground loader

LI / SPEED SYMBOL 218A2

PLY RATING 40

RIM RECOMMENDED 25.00/3.5

RIM PERMITTED 24.00/3.5



LOAD CAPACITY FOR UNDERGROUND LOADER, LB

Pressure (psi)	Speed (mph)			
	0	creep	2.5	5
44	54190	44025	38605	33865
47	56780	46145	40455	35495
51	59305	48180	42250	37060
54	61740	50165	43995	38590
58	64120	52095	45680	40070
62	66435	53980	47335	41525
65	68695	55810	48945	42935
69	70900	57605	50520	44315
73	73060	59360	52050	45660
76	75180	61080	53560	46980
80	77250	62765	55040	48280
83	79280	64420	56495	49550
87	81285	66040	57915	50805
91	83245	67640	59315	52030

TIRE DIMENSIONS

	New tire	Max. in service
OVERALL DIAMETER	79.5 in	83.7 in
TIRE WIDTH	30.2 in	32.8 in
PATTERN DEPTH	123/32 in	
MAX. INFLATION PRESSURE	116 psi	

STATIC LOADED RADIUS	36.4 in @ 52000 lb / 91 psi
DYNAMIC ROLLING CIRCUMFERENCE	241.9 in @ 52000 lb / 91 psi
DYNAMIC ROLLING RADIUS	38.5 in @ 52000 lb / 91 psi
TUBELESS VALVE	TR650
VOLUME	262 gallons 100% 197 gallons 75%

WATER AND SALT BALLASTING

(CaCl₂, 75%, -30°C) Always use a tube when filled with water/salt.

Tire volume 100%		Water filling 75%		Water/salt filling (75% / -30°C)				Total weight increase	
				Water		Salt			
Litres	Gallons	Litres	Gallons	Litres	Gallons	kg	lbs	kg	lbs
991	262	743	196	610	161	311	685	921	2030

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

Tyre have been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/