

# 16.00-25 36 HTS G2 E-4 TL

Keeps the goods moving – efficiently and economically

|                          |                           |
|--------------------------|---------------------------|
| PRODUCT CODE             | T445711                   |
| TIRE CLASSIFICATION CODE | E-4                       |
| APPLICATION              | Reach stacker / Fork lift |
| LI / SPEED SYMBOL        | 199A5                     |
| PLY RATING               | 36                        |
| RIM RECOMMENDED          | 11.25/2.0                 |
| RIM PERMITTED            | 11.25/2.0 IF, 13.00/2.0   |



## LOAD CAPACITY FOR REACH STACKER, LB

### Load wheel

| Pressure (psi) | Speed (mph) |       |       |       |       |       |
|----------------|-------------|-------|-------|-------|-------|-------|
|                | 0           | creep | 2.5   | 5     | 12    | 15    |
| 145            | 44975       | 38980 | 38980 | 38980 | 38980 | 38980 |

### Steer wheel

| Pressure (psi) | Speed (mph) |       |       |       |       |       |
|----------------|-------------|-------|-------|-------|-------|-------|
|                | 0           | creep | 2.5   | 5     | 12    | 15    |
| 145            | 35980       | 31480 | 31480 | 31480 | 29985 | 29985 |

## TIRE DIMENSIONS

|                         | New tire | Max. in service |
|-------------------------|----------|-----------------|
| OVERALL DIAMETER        | 60.5 in  | 61.1 in         |
| TIRE WIDTH              | 17.8 in  | 18.4 in         |
| PATTERN DEPTH           | 72/32 in |                 |
| MAX. INFLATION PRESSURE | 145 psi  |                 |

|                               |                                   |
|-------------------------------|-----------------------------------|
| STATIC LOADED RADIUS          | 27.3 in @ 30000 lb / 145 psi      |
| DYNAMIC ROLLING CIRCUMFERENCE | 181.3 in @ 30000 lb / 145 psi     |
| DYNAMIC ROLLING RADIUS        | 28.9 in @ 30000 lb / 145 psi      |
| TUBE PRODUCT CODE             | T55810                            |
| TUBE VALVE                    | TRJ1175                           |
| TUBELESS VALVE                | TR650                             |
| STUDDABLE                     | Yes                               |
| VOLUME                        | 83 gallons 100%<br>62 gallons 75% |

## WATER AND SALT BALLASTING

(CaCl<sub>2</sub>, 75%, -30°C) Always use a tube when filled with water/salt.

| Tire volume 100% |         | Water filling 75% |         | Water/salt filling (75% / -30°C) |         |      |     | Total weight increase |     |
|------------------|---------|-------------------|---------|----------------------------------|---------|------|-----|-----------------------|-----|
|                  |         |                   |         | Water                            |         | Salt |     |                       |     |
| Litres           | Gallons | Litres            | Gallons | Litres                           | Gallons | kg   | lbs | kg                    | lbs |
| 314              | 83      | 236               | 62      | 193                              | 51      | 99   | 217 | 292                   | 644 |

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

Tyre have been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

**More information:** [www.nokiantyres.com/heavy/technical-tire-manual/](http://www.nokiantyres.com/heavy/technical-tire-manual/)