

18.00-25 40 207A5 NOKIAN TYRES HTS G2 L-5S TL

Reach stacker tire that is made to last

PRODUCT CODE	T445805
TIRE CLASSIFICATION CODE	L-5S
APPLICATION	Reach stacker load axle use
LI / SPEED SYMBOL	207A5
PLY RATING	40
RIM RECOMMENDED	13.00/2.5
RIM PERMITTED	13.00/2.5 IF, 15.00/2.5



LOAD CAPACITY FOR REACH STACKER LOAD AXLE USE, KG

Load wheel

Pressure (kPa)	Speed (km/h)					
	0	1	5	10	20	25
1000	26250	22750	22750	22750	22750	22750

TIRE DIMENSIONS

	New tire	Max. in service
OVERALL DIAMETER	1669 mm	1680 mm
TIRE WIDTH	524 mm	538 mm
PATTERN DEPTH	79 mm	
MAX. INFLATION PRESSURE	1000 kPa	

STATIC LOADED RADIUS 745 mm @ 17500 kg / 1000 kPa

DYNAMIC ROLLING CIRCUMFERENCE 5032 mm @ 17500 kg / 1000 kPa

DYNAMIC ROLLING RADIUS 801 mm @ 17500 kg / 1000 kPa

TUBE PRODUCT CODE T55831

TUBE VALVE TR J1175

TUBELESS VALVE TR650

STUDDABLE Yes

VOLUME 405 l 100%
304 l 75%

WATER AND SALT BALLASTING

(CaCl₂, 75%, -30°C) Always use a tube when filled with water/salt.

Tire volume 100%		Water filling 75%		Water/salt filling (75% / -30°C)				Total weight increase	
				Water		Salt			
Litres	Gallons	Litres	Gallons	Litres	Gallons	kg	lbs	kg	lbs
405	107	304	80	249	66	127	280	376	829

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

Tyre have been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/