

600/50-22.5 20 FOREST KING TRS 2 SF TT

Excellent traction in most demanding forestry use

PRODUCT CODE	T445618
TIRE CLASSIFICATION CODE	LS-2
APPLICATION	Forwarder and Harvester
LI / SPEED SYMBOL	159A8 (167A2)
PLY RATING	20
RIM RECOMMENDED	AG20.00
TYPE APPROVAL	E8 106R-001584



LOAD CAPACITY FOR FORWARDER AND HARVESTER, LB

Forestry service (LT)

Pressure (psi)	Speed (mph)
	5
23	6010
29	6780
35	7385
41	8265
46	8820
52	9645
58	10470
65	11025
73	12015

Road

Pressure (psi)	Speed (mph)		
	12	17.5	25
23	6075	5280	4940
29	6780	5895	5510
35	7385	6425	6010
41	8335	7255	6780
46	8820	7670	7165
52	9625	8380	7825
58	10505	9140	8545
65	11190	9735	9095
73	11860	10320	9645

TIRE DIMENSIONS

	New tire	Max. in service
OVERALL DIAMETER	46 in	47.8 in
TIRE WIDTH	23.5 in	25.1 in
PATTERN DEPTH	53/32 in	
MAX. INFLATION PRESSURE	80 psi	

STATIC LOADED RADIUS 21 in @ 12000 lb / 73 psi

DYNAMIC ROLLING CIRCUMFERENCE 139.8 in @ 12000 lb / 73 psi

DYNAMIC ROLLING RADIUS 22.2 in @ 12000 lb / 73 psi

TUBE PRODUCT CODE T55089

TUBE VALVE TR218A

BREAKER MATERIAL Steel

VOLUME 79 gallons 100%
59 gallons 75%

WATER AND SALT BALLASTING

(CaCl₂, 75%, -30°C) Always use a tube when filled with water/salt.

Tire volume 100%		Water filling 75%		Water/salt filling (75% / -30°C)				Total weight increase	
				Water		Salt			
Litres	Gallons	Litres	Gallons	Litres	Gallons	kg	lbs	kg	lbs
300	79	225	59	185	49	94	207	279	615

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

Tyre have been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/