

600/50-24.5 20 164A8/171A2 NOKIAN TYRES FOREST KING TRS 2 SF TT

Excellent traction in most demanding forestry use

PRODUCT CODE	T445639
TIRE CLASSIFICATION CODE	LS-2
APPLICATION	Forwarder and Harvester
LI / SPEED SYMBOL	164A8 (171A2)
PLY RATING	20
RIM RECOMMENDED	AG20.00
RIM PERMITTED	AG22.00
TYPE APPROVAL	E8 106R-001585



LOAD CAPACITY FOR FORWARDER AND HARVESTER, KG

Forestry service (LT)

Pressure (kPa)	Speed (km/h)
	10
160	2900
200	3150
240	3450
280	3875
320	4125
360	4500
400	4875
450	5300
500	5600

Road

Pressure (kPa)	Speed (km/h)		
	20	30	40
160	2905	2525	2360
200	3165	2755	2575
240	3445	2995	2800
280	3875	3370	3150
320	4120	3585	3350
360	4490	3905	3650
400	4920	4280	4000
450	5230	4550	4250
500	5535	4815	4500

TYRE DIMENSIONS

	New tire	Max. in service
OVERALL DIAMETER	1230 mm	1264 mm
TYRE WIDTH	603 mm	638 mm
PATTERN DEPTH	48 mm	
MAX. INFLATION PRESSURE	550 kPa	

STATIC LOADED RADIUS	566 mm @ 6150 kg / 550 kPa
DYNAMIC ROLLING CIRCUMFERENCE	3738 mm @ 6150 kg / 550 kPa
DYNAMIC ROLLING RADIUS	595 mm @ 6150 kg / 550 kPa
TUBE PRODUCT CODE	T545447
TUBE VALVE	TR218A
BREAKER MATERIAL	Steel
VOLUME	320 l 100% 240 l 75%

WATER AND SALT BALLASTING

(CaCl₂, 75%, -30°C) Always use a tube when filled with water/salt.

Tire volume 100%		Water filling 75%		Water/salt filling (75% / -30°C)				Total weight increase	
				Water		Salt			
Litres	Gallons	Litres	Gallons	Litres	Gallons	kg	lbs	kg	lbs
320	85	240	63	197	52	100	221	297	655

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

Tyre have been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/