

780/50-28.5 24 FOREST KING TRS 2 SF TT

Excellent traction in most demanding forestry use

PRODUCT CODE	T445581
TIRE CLASSIFICATION CODE	LS-2
APPLICATION	Forwarder and Harvester
LI / SPEED SYMBOL	182A8 (190A2)
PLY RATING	24
RIM RECOMMENDED	AG26.00
TYPE APPROVAL	E8 106R-001579



LOAD CAPACITY FOR FORWARDER AND HARVESTER, KG

Forestry service (LT)

Pressure (kPa)	Speed (km/h)
	10
160	4625
200	5300
240	5600
280	6300
320	6500
360	7300
400	8000
450	8500
500	9000
600	10600

Road

Pressure (kPa)	Speed (km/h)		
	20	30	40
160	4615	4015	3750
200	5230	4550	4250
240	5535	4815	4500
280	6335	5510	5150
320	6520	5670	5300
360	7380	6420	6000
400	7995	6955	6500
450	8485	7385	6900
500	8980	7810	7300
600	10455	9095	8500

TIRE DIMENSIONS

	New tire	Max. in service
OVERALL DIAMETER	1513 mm	1558 mm
TIRE WIDTH	782 mm	836 mm
PATTERN DEPTH	49 mm	
MAX. INFLATION PRESSURE	600 kPa	

STATIC LOADED RADIUS 691 mm @ 10600 kg / 600 kPa

DYNAMIC ROLLING CIRCUMFERENCE 4611 mm @ 10600 kg / 600 kPa

DYNAMIC ROLLING RADIUS 734 mm @ 10600 kg / 600 kPa

TUBE PRODUCT CODE T545543

TUBE VALVE TR218A

BREAKER MATERIAL Steel

VOLUME 675 l 100%
506 l 75%

WATER AND SALT BALLASTING

(CaCl₂, 75%, -30°C) Always use a tube when filled with water/salt.

Tire volume 100%		Water filling 75%		Water/salt filling (75% / -30°C)				Total weight increase	
				Water		Salt			
Litres	Gallons	Litres	Gallons	Litres	Gallons	kg	lbs	kg	lbs
675	178	506	134	415	110	212	467	627	1382

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

Tyre have been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/