

800/40-26.5 20 FOREST KING TRS 2 SF TT

Excellent traction in most demanding forestry use

PRODUCT CODE	T445594
TIRE CLASSIFICATION CODE	LS-2
APPLICATION	Forwarder and Harvester
LI / SPEED SYMBOL	170A8 (177A2)
PLY RATING	20
RIM RECOMMENDED	AG28.00
TYPE APPROVAL	E8 106R-001580



LOAD CAPACITY FOR FORWARDER AND HARVESTER, LB

Forestry service (LT)

Pressure (psi)	Speed (mph)
	5
23	8545
29	9370
35	10195
41	11685
46	12015
52	13230
58	14330
65	15655
73	16095

Road

Pressure (psi)	Speed (mph)		
	12	17.5	25
23	8545	7430	6945
29	9360	8135	7605
35	10175	8850	8265
41	11530	10030	9370
46	11860	10320	9645
52	13215	11495	10750
58	14375	12500	11685
65	15730	13680	12785
73	16270	14155	13230

TIRE DIMENSIONS

	New tire	Max. in service
OVERALL DIAMETER	52.9 in	53.4 in
TIRE WIDTH	31.4 in	35.2 in
PATTERN DEPTH	60/32 in	
MAX. INFLATION PRESSURE	80 psi	

STATIC LOADED RADIUS 24.4 in @ 16100 lb / 73 psi

DYNAMIC ROLLING CIRCUMFERENCE 161.3 in @ 16100 lb / 73 psi

DYNAMIC ROLLING RADIUS 25.7 in @ 16100 lb / 73 psi

TUBE PRODUCT CODE T545312

TUBE VALVE TR218A

BREAKER MATERIAL Steel

VOLUME 151 gallons 100%
113 gallons 75%

WATER AND SALT BALLASTING

(CaCl₂, 75%, -30°C) Always use a tube when filled with water/salt.

Tire volume 100%		Water filling 75%		Water/salt filling (75% / -30°C)				Total weight increase	
				Water		Salt			
Litres	Gallons	Litres	Gallons	Litres	Gallons	kg	lbs	kg	lbs
570	151	428	113	351	93	179	394	530	1168

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

Tyre have been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/