

600/65-34 24 169A8/176A2 NOKIAN TYRES FOREST KING TRS 2PLUS SF TT

Soil-friendly traction for 6-wheel forwarders and harvesters – with or without tracks

| | |
|--------------------------|--|
| PRODUCT CODE | T445714 |
| TIRE CLASSIFICATION CODE | LS-2 |
| APPLICATION | Forwarder and Harvester / Backhoe loader |
| LI / SPEED SYMBOL | 169A8 (176A2) |
| PLY RATING | 24 |
| RIM RECOMMENDED | DW20B |
| TYPE APPROVAL | E8 106R-001749 |



LOAD CAPACITY FOR FORWARDER AND HARVESTER, LB

Forestry service (LT)

| Pressure (psi) | Speed (mph) |
|----------------|-------------|
| | 5 |
| 23 | 9645 |
| 29 | 10470 |
| 35 | 11025 |
| 41 | 12345 |
| 46 | 13230 |
| 52 | 14330 |
| 58 | 15655 |

Road

| Pressure (psi) | Speed (mph) | | | | |
|----------------|-------------|-------|-------|-------|-------|
| | 5 | 12 | 17.5 | 25 | 30 |
| 23 | 11740 | 9625 | 8380 | 7825 | 7120 |
| 29 | 12820 | 10505 | 9140 | 8545 | 7770 |
| 35 | 13645 | 11190 | 9735 | 9095 | 8280 |
| 41 | 15300 | 12545 | 10915 | 10195 | 9280 |
| 46 | 16125 | 13215 | 11495 | 10750 | 9780 |
| 52 | 17525 | 14375 | 12500 | 11685 | 10635 |
| 58 | 19180 | 15730 | 13680 | 12785 | 11640 |

TIRE DIMENSIONS

| | New tire | Max. in service |
|-------------------------|----------|-----------------|
| OVERALL DIAMETER | 64.5 in | 66.9 in |
| TIRE WIDTH | 24.2 in | 25.6 in |
| PATTERN DEPTH | 63/32 in | |
| MAX. INFLATION PRESSURE | 58 psi | |

STATIC LOADED RADIUS 29.3 in @ 15700 lb / 58 psi

DYNAMIC ROLLING CIRCUMFERENCE 195.4 in @ 15700 lb / 58 psi

DYNAMIC ROLLING RADIUS 31.1 in @ 15700 lb / 58 psi

TUBE PRODUCT CODE T55394

TUBE VALVE TR218A

BREAKER MATERIAL Steel

VOLUME 149 gallons 100%
112 gallons 75%

WATER AND SALT BALLASTING

(CaCl₂, 75%, -30°C) Always use a tube when filled with water/salt.

| Tire volume 100% | | Water filling 75% | | Water/salt filling (75% / -30°C) | | | | Total weight increase | |
|------------------|---------|-------------------|---------|----------------------------------|---------|------|-----|-----------------------|------|
| | | | | Water | | Salt | | | |
| Litres | Gallons | Litres | Gallons | Litres | Gallons | kg | lbs | kg | lbs |
| 565 | 149 | 424 | 112 | 348 | 92 | 177 | 391 | 525 | 1157 |

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

Tyre have been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/