

# 600/65-34 20 163A8/170A2 NOKIAN TYRES NORDMAN FOREST TRS L-2 SF TT

Excellent traction for replacement market

PRODUCT CODE	T445475
TIRE CLASSIFICATION CODE	LS-2
APPLICATION	Forwarder and Harvester
LI / SPEED SYMBOL	163A8 (170A2)
PLY RATING	20
RIM RECOMMENDED	DW20B
TYPE APPROVAL	E8 106R-001659



## LOAD CAPACITY FOR FORWARDER AND HARVESTER, KG

### Forestry service (LT)

Pressure (kPa)	Speed (km/h)
	10
160	4375
200	4750
240	5000
280	5600
320	6000

### Road

Pressure (kPa)	Speed (km/h)		
	20	30	40
160	4365	3800	3550
200	4765	4145	3875
240	5075	4415	4125
280	5690	4950	4625
320	5995	5215	4875

## TIRE DIMENSIONS

	New tire	Max. in service
OVERALL DIAMETER	1644 mm	1698 mm
TIRE WIDTH	615 mm	649 mm
PATTERN DEPTH	51 mm	
MAX. INFLATION PRESSURE	360 kPa	

STATIC LOADED RADIUS 755 mm @ 6000 kg / 320 kPa

DYNAMIC ROLLING CIRCUMFERENCE 4964 mm @ 6000 kg / 320 kPa

DYNAMIC ROLLING RADIUS 790 mm @ 6000 kg / 320 kPa

TUBE PRODUCT CODE T55394

TUBE VALVE TR218A

BREAKER MATERIAL Steel

VOLUME 595 l 100%  
446 l 75%

**WATER AND SALT BALLASTING**

(CaCl<sub>2</sub>, 75%, -30°C) Always use a tube when filled with water/salt.

Tire volume 100%		Water filling 75%		Water/salt filling (75% / -30°C)				Total weight increase	
				Water		Salt			
Litres	Gallons	Litres	Gallons	Litres	Gallons	kg	lbs	kg	lbs
595	157	446	118	366	97	187	412	553	1219

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

Tyre have been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: [www.nokiantyres.com/heavy/technical-tire-manual/](http://www.nokiantyres.com/heavy/technical-tire-manual/)