

# 600/65-34 20 163A8/170A2 NOKIAN TYRES NORDMAN FOREST TRS L-2 SF TT

Excellent traction for replacement market

PRODUCT CODE	T445475
TIRE CLASSIFICATION CODE	LS-2
APPLICATION	Forwarder and Harvester
LI / SPEED SYMBOL	163A8 (170A2)
PLY RATING	20
RIM RECOMMENDED	DW20B
TYPE APPROVAL	E8 106R-001659



## LOAD CAPACITY FOR FORWARDER AND HARVESTER, LB

### Forestry service (LT)

Pressure (psi)	Speed (mph)
	5
23	9645
29	10470
35	11025
41	12345
46	13230

### Road

Pressure (psi)	Speed (mph)		
	12	17.5	25
23	9625	8380	7825
29	10505	9140	8545
35	11190	9735	9095
41	12545	10915	10195
46	13215	11495	10750

## TIRE DIMENSIONS

	New tire	Max. in service
OVERALL DIAMETER	64.7 in	66.9 in
TIRE WIDTH	24.2 in	25.6 in
PATTERN DEPTH	64/32 in	
MAX. INFLATION PRESSURE	52 psi	

STATIC LOADED RADIUS	29.7 in @ 13200 lb / 46 psi
DYNAMIC ROLLING CIRCUMFERENCE	195.4 in @ 13200 lb / 46 psi
DYNAMIC ROLLING RADIUS	31.1 in @ 13200 lb / 46 psi
TUBE PRODUCT CODE	T55394
TUBE VALVE	TR218A
BREAKER MATERIAL	Steel
VOLUME	157 gallons 100% 118 gallons 75%

**WATER AND SALT BALLASTING**

(CaCl<sub>2</sub>, 75%, -30°C) Always use a tube when filled with water/salt.

Tire volume 100%		Water filling 75%		Water/salt filling (75% / -30°C)				Total weight increase	
				Water		Salt			
Litres	Gallons	Litres	Gallons	Litres	Gallons	kg	lbs	kg	lbs
595	157	446	118	366	97	187	412	553	1219

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

Tyre have been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: [www.nokiantyres.com/heavy/technical-tire-manual/](http://www.nokiantyres.com/heavy/technical-tire-manual/)