

600/65R34 157A8/154B TR MULTIPLUS TL

Radial tire for multi-purpose use

PRODUCT CODE	T445413
TIRE CLASSIFICATION CODE	R-1
APPLICATION	Tractor
LI / SPEED SYMBOL	157A8 (154B)
RIM RECOMMENDED	DW18L
RIM PERMITTED	W16L, W18L, DW20B, DW 16 L
TYPE APPROVAL	106R-001811



LOAD CAPACITY FOR TRACTOR, KG

Tractor

Pressure (kPa)	Speed (km/h)										
	0	5	10	15	20	25	30	35	40	45	50
120	6670	4930	4350	3885	3565	3220	3105	2985	2900	2785	2640
160	7935	5865	5175	4625	4245	3830	3690	3555	3450	3310	3140
200	8915	6590	5815	5195	4765	4300	4145	3990	3875	3720	3525
240	9490	7015	6190	5530	5075	4580	4415	4250	4125	3960	3755

TIRE DIMENSIONS

	New tire	Max. in service
OVERALL DIAMETER	1640 mm	1676 mm
TIRE WIDTH	585 mm	621 mm
PATTERN DEPTH	52 mm	
MAX. INFLATION PRESSURE	320 kPa	

STATIC LOADED RADIUS	750 mm @ 4125 kg / 240 kPa
DYNAMIC ROLLING CIRCUMFERENCE	4930 mm @ 4125 kg / 240 kPa
DYNAMIC ROLLING RADIUS	785 mm @ 4125 kg / 240 kPa
SPEED RADIUS INDEX	775
TUBE PRODUCT CODE	T55395
TUBE VALVE	TR218A
TUBELESS VALVE	TR618A
BELT MATERIAL	Steel
STUDDABLE	Yes Number of studs 108 pcs
VOLUME	575 l 100% 431 l 75%

WATER AND SALT BALLASTING

(CaCl₂, 75%, -30°C) Always use a tube when filled with water/salt.

Tire volume 100%		Water filling 75%		Water/salt filling (75% / -30°C)				Total weight increase	
				Water		Salt			
Litres	Gallons	Litres	Gallons	Litres	Gallons	kg	lbs	kg	lbs
575	152	431	114	354	93	180	398	534	1177

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

Tyre have been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/