

560/60R22.5 165D CT TL

Stability for transporting high loads

PRODUCT CODE	T445626
APPLICATION	Trailer
LI / SPEED SYMBOL	165D
RIM RECOMMENDED	AG18.00
RIM PERMITTED	AG 16.00
TYPE APPROVAL	E8 106R-001194



LOAD CAPACITY FOR TRAILER, KG

Mixed

Pressure (kPa)	Speed (km/h)											
	10	15	20	25	30	35	40	45	50	55	60	65
80	2790	2680	2560	2450	2340	2230	2110	2000	1875	1765	1660	1550
120	3510	3375	3220	3080	2945	2810	2650	2515	2360	2225	2085	1950
160	4375	4205	4010	3840	3670	3500	3305	3135	2940	2770	2600	2430
200	4770	4585	4375	4185	4000	3815	3605	3420	3205	3020	2835	2650
240	5535	5320	5075	4860	4645	4430	4180	3965	3720	3505	3290	3075
280	6210	5970	5695	5450	5210	4970	4690	4450	4175	3935	3690	3450
320	6975	6705	6395	6125	5850	5580	5270	5000	4690	4420	4145	3875
360	7650	7355	7015	6715	6420	6120	5780	5485	5145	4845	4550	4250
400	8325	8000	7630	7310	6985	6660	6290	5965	5595	5275	4950	4625
450	8775	8435	8045	7705	7360	7020	6630	6290	5900	5560	5215	4875
500	9270	8910	8500	8135	7775	7415	7005	6645	6230	5870	5510	5150

TIRE DIMENSIONS

	New tire	Max. in service
OVERALL DIAMETER	1245 mm	1270 mm
TIRE WIDTH	560 mm	570 mm
PATTERN DEPTH	22 mm	
MAX. INFLATION PRESSURE	500 kPa	

STATIC LOADED RADIUS	555 mm @ 5150 kg / 500 kPa
DYNAMIC ROLLING CIRCUMFERENCE	3811 mm @ 5150 kg / 500 kPa
DYNAMIC ROLLING RADIUS	607 mm @ 5150 kg / 500 kPa
SPEED RADIUS INDEX	600
TUBE PRODUCT CODE	T55098
TUBE VALVE	TR218A
TUBELESS VALVE	TR618A
BELT MATERIAL	Steel
VOLUME	390 l 100% 293 l 75%

WATER AND SALT BALLASTING

(CaCl₂, 75%, -30°C) Always use a tube when filled with water/salt.

Tire volume 100%		Water filling 75%		Water/salt filling (75% / -30°C)				Total weight increase	
				Water		Salt			
Litres	Gallons	Litres	Gallons	Litres	Gallons	kg	lbs	kg	lbs
390	103	293	77	240	63	122	270	362	798

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

Tyre have been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/