

650/65R26.5 174D ELS SB TL

Light touch for the environment

PRODUCT CODE	T445465
APPLICATION	Trailer / Tractor
LI / SPEED SYMBOL	174D
RIM RECOMMENDED	AG20.00
TYPE APPROVAL	E8 106R-001188



LOAD CAPACITY FOR TRAILER, LB

Mixed

Pressure (psi)	Speed (mph)											
	5	10	12	15	17.5	22.5	25	27.5	30	35	37.5	40
12	9125	8775	8365	8015	7660	7295	6900	6535	6140	5775	5425	5070
17	11510	11055	10550	10095	9655	9205	8695	8245	7740	7285	6845	6395
23	13690	13160	12555	12015	11485	10955	10340	9810	9205	8675	8135	7605
29	15375	14780	14100	13505	12895	12300	11620	11025	10340	9745	9140	8545
35	17855	17165	16370	15675	14980	14285	13490	12800	12005	11310	10615	9920
41	20435	19645	18740	17935	17140	16345	15445	14650	13735	12940	12145	11355
46	22225	21365	20370	19510	18640	17780	16790	15930	14935	14075	13205	12345
52	24405	23455	22375	21420	20470	19520	18440	17495	16400	15455	14505	13560
58	26590	25550	24370	23335	22300	21275	20085	19060	17870	16845	15805	14770

TIRE DIMENSIONS

	New tire	Max. in service
OVERALL DIAMETER	59.6 in	61.1 in
TIRE WIDTH	25.4 in	26.7 in
PATTERN DEPTH	30/32 in	
MAX. INFLATION PRESSURE	58 psi	

STATIC LOADED RADIUS	26.8 in @ 14800 lb / 58 psi
DYNAMIC ROLLING CIRCUMFERENCE	181.8 in @ 14800 lb / 58 psi
DYNAMIC ROLLING RADIUS	28.9 in @ 14800 lb / 58 psi
SPEED RADIUS INDEX	725
TUBE PRODUCT CODE	T55102
TUBE VALVE	TR218A
TUBELESS VALVE	TR618A
BELT MATERIAL	Steel
VOLUME	192 gallons 100% 144 gallons 75%

WATER AND SALT BALLASTING

(CaCl₂, 75%, -30°C) Always use a tube when filled with water/salt.

Tire volume 100%		Water filling 75%		Water/salt filling (75% / -30°C)				Total weight increase	
				Water		Salt			
Litres	Gallons	Litres	Gallons	Litres	Gallons	kg	lbs	kg	lbs
725	192	544	144	446	118	227	501	673	1484

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

Tyre have been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/