

460/70R24 166A8/161D HAKKAPELIITTA TRI TL

Precise control and great efficiency

| | |
|--------------------------|------------------------|
| PRODUCT CODE | T445669 |
| TIRE CLASSIFICATION CODE | R-4 |
| APPLICATION | Tractor / Wheel loader |
| LI / SPEED SYMBOL | 166A8 (161D) |
| RIM RECOMMENDED | DW14L |
| RIM PERMITTED | DW15L |
| TYPE APPROVAL | E8 106R-001574 |



LOAD CAPACITY FOR TRACTOR, KG

Constant load

| Pressure (kPa) | Speed (km/h) | | | | | | | | | | | | | |
|----------------|--------------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| | 0 | 5 | 10 | 15 | 20 | 25 | 30 | 35 | 40 | 45 | 50 | 55 | 60 | 65 |
| 80 | 3695 | 2340 | 2015 | 1820 | 1765 | 1710 | 1680 | 1650 | 1610 | 1570 | 1510 | 1470 | 1440 | 1400 |
| 120 | 4750 | 3005 | 2590 | 2340 | 2270 | 2195 | 2160 | 2125 | 2070 | 2015 | 1945 | 1890 | 1855 | 1800 |
| 160 | 5755 | 3640 | 3140 | 2835 | 2745 | 2660 | 2615 | 2570 | 2505 | 2440 | 2355 | 2290 | 2245 | 2180 |
| 200 | 6415 | 4060 | 3500 | 3160 | 3060 | 2965 | 2915 | 2865 | 2795 | 2720 | 2625 | 2550 | 2505 | 2430 |
| 240 | 6800 | 4300 | 3710 | 3350 | 3245 | 3140 | 3090 | 3040 | 2960 | 2885 | 2780 | 2705 | 2650 | 2575 |
| 280 | 7390 | 4675 | 4030 | 3640 | 3530 | 3415 | 3360 | 3305 | 3220 | 3135 | 3025 | 2940 | 2885 | 2800 |
| 320 | 8315 | 5260 | 4535 | 4095 | 3970 | 3845 | 3780 | 3715 | 3625 | 3530 | 3400 | 3310 | 3245 | 3150 |
| 360 | 9110 | 5760 | 4970 | 4485 | 4345 | 4210 | 4140 | 4070 | 3970 | 3865 | 3725 | 3625 | 3555 | 3450 |
| 400 | 9900 | 6265 | 5400 | 4875 | 4725 | 4575 | 4500 | 4425 | 4315 | 4200 | 4050 | 3940 | 3865 | 3750 |

Cyclic load

| Pressure (kPa) | Speed (km/h) | | | | | | | | | | | | | |
|-------------------|--------------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| | 0 | 5 | 10 | 15 | 20 | 25 | 30 | 35 | 40 | 45 | 50 | 55 | 60 | 65 |
| 80 | 3695 | 2690 | 2420 | 2155 | 1990 | 1790 | 1720 | 1665 | 1610 | 1570 | 1510 | 1470 | 1440 | 1400 |
| 120 | 4750 | 3455 | 3115 | 2770 | 2555 | 2305 | 2215 | 2140 | 2070 | 2015 | 1945 | 1890 | 1855 | 1800 |
| 160 | 5755 | 4185 | 3770 | 3355 | 3095 | 2790 | 2680 | 2595 | 2505 | 2440 | 2355 | 2290 | 2245 | 2180 |
| 200 | 6415 | 4665 | 4205 | 3740 | 3450 | 3110 | 2990 | 2890 | 2795 | 2720 | 2625 | 2550 | 2505 | 2430 |
| 240 | 6800 | 4945 | 4455 | 3965 | 3655 | 3295 | 3165 | 3065 | 2960 | 2885 | 2780 | 2705 | 2650 | 2575 |
| 280 | 7390 | 5375 | 4845 | 4310 | 3975 | 3585 | 3445 | 3330 | 3220 | 3135 | 3025 | 2940 | 2885 | 2800 |
| 320 | 8315 | 6050 | 5450 | 4850 | 4475 | 4030 | 3875 | 3750 | 3625 | 3530 | 3400 | 3310 | 3245 | 3150 |
| 360 | 9110 | 6625 | 5970 | 5315 | 4900 | 4415 | 4245 | 4105 | 3970 | 3865 | 3725 | 3625 | 3555 | 3450 |
| 400 | 9900 | 7200 | 6490 | 5775 | 5325 | 4800 | 4615 | 4465 | 4315 | 4200 | 4050 | 3940 | 3865 | 3750 |

TIRE DIMENSIONS

| | New tire | Max. in service |
|-------------------------|----------|-----------------|
| OVERALL DIAMETER | 1255 mm | 1280 mm |
| TIRE WIDTH | 460 mm | 478 mm |
| PATTERN DEPTH | 30 mm | |
| MAX. INFLATION PRESSURE | 500 kPa | |

STATIC LOADED RADIUS 557 mm @ 5300 kg / 500 kPa

DYNAMIC ROLLING CIRCUMFERENCE 3792 mm @ 5300 kg / 500 kPa

DYNAMIC ROLLING RADIUS 604 mm @ 5300 kg / 500 kPa

SPEED RADIUS INDEX 600

TUBELESS VALVE TR618A

BELT MATERIAL Steel

MARKINGS M+S

STUDDABLE Yes
Marked stud positions on tread
Number of studs 144 pcs
Recommended stud 12-20,12-23,12-24

VOLUME 290 l 100%
218 l 75%

WATER AND SALT BALLASTING

(CaCl₂, 75%, -30°C) Always use a tube when filled with water/salt.

| Tire volume 100% | | Water filling 75% | | Water/salt filling (75% / -30°C) | | | | Total weight increase | |
|------------------|---------|-------------------|---------|----------------------------------|---------|------|-----|-----------------------|-----|
| | | | | Water | | Salt | | | |
| Litres | Gallons | Litres | Gallons | Litres | Gallons | kg | lbs | kg | lbs |
| 290 | 77 | 218 | 57 | 178 | 47 | 91 | 201 | 269 | 593 |

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

Tyre have been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/