

540/65R30 171A8/166D NOKIAN TYRES HAKKAPELIITTA TRI TL

Precise control and great efficiency

| | |
|--------------------------|----------------|
| PRODUCT CODE | T445736 |
| TIRE CLASSIFICATION CODE | R-4 |
| APPLICATION | Tractor |
| LI / SPEED SYMBOL | 171A8 (166D) |
| RIM RECOMMENDED | DW18L |
| RIM PERMITTED | DW16L |
| TYPE APPROVAL | E8 106R-001741 |



LOAD CAPACITY FOR TRACTOR, KG

Constant load

| Pressure (kPa) | Speed (km/h) | | | | | | | | | | | | | |
|----------------|--------------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| | 0 | 5 | 10 | 15 | 20 | 25 | 30 | 35 | 40 | 45 | 50 | 55 | 60 | 65 |
| 80 | 4750 | 3005 | 2590 | 2340 | 2270 | 2195 | 2160 | 2125 | 2070 | 2015 | 1945 | 1890 | 1855 | 1800 |
| 120 | 6070 | 3840 | 3310 | 2990 | 2900 | 2805 | 2760 | 2715 | 2645 | 2575 | 2485 | 2415 | 2370 | 2300 |
| 160 | 7195 | 4550 | 3925 | 3545 | 3435 | 3325 | 3270 | 3215 | 3135 | 3050 | 2945 | 2860 | 2805 | 2725 |
| 200 | 8120 | 5135 | 4430 | 4000 | 3875 | 3750 | 3690 | 3630 | 3535 | 3445 | 3320 | 3230 | 3165 | 3075 |
| 240 | 8845 | 5595 | 4825 | 4355 | 4220 | 4085 | 4020 | 3955 | 3855 | 3750 | 3620 | 3520 | 3450 | 3350 |
| 280 | 9635 | 6095 | 5255 | 4745 | 4600 | 4455 | 4380 | 4305 | 4200 | 4090 | 3940 | 3835 | 3760 | 3650 |
| 320 | 10560 | 6680 | 5760 | 5200 | 5040 | 4880 | 4800 | 4720 | 4600 | 4480 | 4320 | 4200 | 4120 | 4000 |
| 360 | 11550 | 7305 | 6300 | 5690 | 5515 | 5340 | 5250 | 5165 | 5030 | 4900 | 4725 | 4595 | 4505 | 4375 |
| 400 | 12870 | 8140 | 7020 | 6340 | 6145 | 5950 | 5850 | 5755 | 5605 | 5460 | 5265 | 5120 | 5020 | 4875 |

Cyclic load

| Pressure (kPa) | Speed (km/h) | | | | | | | | | | | | | |
|----------------|--------------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| | 0 | 5 | 10 | 15 | 20 | 25 | 30 | 35 | 40 | 45 | 50 | 55 | 60 | 65 |
| 80 | 4750 | 3455 | 3115 | 2770 | 2555 | 2305 | 2215 | 2140 | 2070 | 2015 | 1945 | 1890 | 1855 | 1800 |
| 120 | 6070 | 4415 | 3980 | 3540 | 3265 | 2945 | 2830 | 2735 | 2645 | 2575 | 2485 | 2415 | 2370 | 2300 |
| 160 | 7195 | 5230 | 4715 | 4195 | 3870 | 3490 | 3350 | 3245 | 3135 | 3050 | 2945 | 2860 | 2805 | 2725 |
| 200 | 8120 | 5905 | 5320 | 4735 | 4365 | 3935 | 3780 | 3660 | 3535 | 3445 | 3320 | 3230 | 3165 | 3075 |
| 240 | 8845 | 6430 | 5795 | 5160 | 4755 | 4290 | 4120 | 3985 | 3855 | 3750 | 3620 | 3520 | 3450 | 3350 |
| 280 | 9635 | 7010 | 6315 | 5620 | 5185 | 4670 | 4490 | 4345 | 4200 | 4090 | 3940 | 3835 | 3760 | 3650 |
| 320 | 10560 | 7680 | 6920 | 6160 | 5680 | 5120 | 4920 | 4760 | 4600 | 4480 | 4320 | 4200 | 4120 | 4000 |
| 360 | 11550 | 8400 | 7570 | 6740 | 6215 | 5600 | 5380 | 5205 | 5030 | 4900 | 4725 | 4595 | 4505 | 4375 |
| 400 | 12870 | 9360 | 8435 | 7510 | 6925 | 6240 | 5995 | 5800 | 5605 | 5460 | 5265 | 5120 | 5020 | 4875 |

TIRE DIMENSIONS

| | New tire | Max. in service |
|-------------------------|----------|-----------------|
| OVERALL DIAMETER | 1460 mm | 1479 mm |
| TIRE WIDTH | 534 mm | 561 mm |
| PATTERN DEPTH | 28 mm | |
| MAX. INFLATION PRESSURE | 450 kPa | |

STATIC LOADED RADIUS 667 mm @ 6150 kg / 450 kPa

DYNAMIC ROLLING CIRCUMFERENCE 4442 mm @ 6150 kg / 450 kPa

DYNAMIC ROLLING RADIUS 707 mm @ 6150 kg / 450 kPa

SPEED RADIUS INDEX 700

TUBELESS VALVE TR618A

BELT MATERIAL Steel

MARKINGS M+S

STUDDABLE Yes
Marked stud positions on tread
Number of studs 168 pcs
Recommended stud 12-20,12-23,12-24

VOLUME 482 l 100%
362 l 75%

WATER AND SALT BALLASTING

(CaCl₂, 75%, -30°C) Always use a tube when filled with water/salt.

| Tire volume 100% | | Water filling 75% | | Water/salt filling (75% / -30°C) | | | | Total weight increase | |
|------------------|---------|-------------------|---------|----------------------------------|---------|------|-----|-----------------------|-----|
| | | | | Water | | Salt | | | |
| Litres | Gallons | Litres | Gallons | Litres | Gallons | kg | lbs | kg | lbs |
| 482 | 127 | 362 | 95 | 297 | 78 | 151 | 333 | 448 | 988 |

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

Tyre have been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/