

600/70R34 172A8/168D HAKKAPELIITTA TRI TL

Precise control and great efficiency

PRODUCT CODE	T445700
TIRE CLASSIFICATION CODE	R-4
APPLICATION	Tractor
LI / SPEED SYMBOL	172A8 (168D)
RIM RECOMMENDED	DW20B
RIM PERMITTED	DW18L
TYPE APPROVAL	E8 106R-001168



LOAD CAPACITY FOR TRACTOR, LB

Constant load

Pressure (psi)	Speed (mph)													
	0	2.5	5	10	12	15	17.5	22.5	25	27.5	30	35	37.5	40
12	14550	9205	7935	7165	6945	6725	6615	6505	6340	6175	5950	5785	5675	5510
17	18330	11595	10000	9030	8750	8475	8335	8190	7990	7780	7495	7295	7155	6945
23	22555	14265	12300	11110	10770	10430	10250	10085	9820	9570	9225	8975	8795	8545
29	24735	15655	13490	12180	11805	11430	11245	11055	10780	10495	10120	9845	9655	9370
35	26190	16570	14285	12895	12500	12105	11905	11705	11410	11110	10715	10415	10220	9920
41	29100	18410	15875	14330	13890	13450	13230	13005	12675	12345	11905	11575	11355	11025
46	32595	20615	17780	16050	15555	15060	14815	14575	14200	13825	13340	12965	12720	12345

Cyclic load

Pressure (psi)	Speed (mph)													
	0	2.5	5	10	12	15	17.5	22.5	25	27.5	30	35	37.5	40
12	14550	10580	9535	8490	7825	7055	6780	6560	6340	6175	5950	5785	5675	5510
17	18330	13340	12015	10690	9865	8885	8545	8265	7990	7780	7495	7295	7155	6945
23	22555	16400	14780	13160	12135	10935	10505	10165	9820	9570	9225	8975	8795	8545
29	24735	17990	16215	14430	13305	11995	11530	11155	10780	10495	10120	9845	9655	9370
35	26190	19050	17165	15280	14090	12700	12205	11805	11410	11110	10715	10415	10220	9920
41	29100	21165	19070	16975	15655	14110	13560	13120	12675	12345	11905	11575	11355	11025
46	32595	23700	21365	19015	17525	15805	15190	14695	14200	13825	13340	12965	12720	12345

TIRE DIMENSIONS

	New tire	Max. in service
OVERALL DIAMETER	66 in	68.4 in
TIRE WIDTH	23.3 in	24.8 in
PATTERN DEPTH	35/32 in	
MAX. INFLATION PRESSURE	46 psi	

STATIC LOADED RADIUS	29.7 in @ 13900 lb / 46 psi
DYNAMIC ROLLING CIRCUMFERENCE	200.9 in @ 13900 lb / 46 psi
DYNAMIC ROLLING RADIUS	32 in @ 13900 lb / 46 psi
SPEED RADIUS INDEX	800
TUBELESS VALVE	TR618A
BELT MATERIAL	Steel
MARKINGS	M+S
STUDDABLE	Yes Marked stud positions on tread Number of studs 168 pcs Recommended stud 12-20,12-23,12-24
VOLUME	188 gallons 100% 141 gallons 75%

WATER AND SALT BALLASTING

(CaCl₂, 75%, -30°C) Always use a tube when filled with water/salt.

Tire volume 100%		Water filling 75%		Water/salt filling (75% / -30°C)				Total weight increase	
				Water		Salt			
Litres	Gallons	Litres	Gallons	Litres	Gallons	kg	lbs	kg	lbs
710	188	533	141	437	115	223	491	660	1455

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

Tyre have been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/