

215/75R17.5 126/124M NOKIAN TYRES E-TRUCK DRIVE

A sturdy tire for drive axle in regional and urban traffic

PRODUCT CODE	T675255
APPLICATION	Drive
LI / SPEED SYMBOL	126/124M
RIM RECOMMENDED	6.00
RIM PERMITTED	6.75
TYPE APPROVAL	E4 0043511, E4 029281 S2WR2



LOAD CAPACITY, KG

Axle fitting	Speed (km/h)	Pressure (kPa)								
		500	525	550	575	600	625	650	675	700
Single	130	2600	2700	2800	2900	3010	3110	3200	3300	3400
Dual	130	4890	5080	5280	5470	5660	5850	6030	6220	6400

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

TIRE DIMENSIONS

OVERALL DIAMETER	763 mm
TIRE WIDTH	213 mm
STATIC LOADED RADIUS	358 mm
ROLLING CIRCUMFERENCE	2319 mm
MIN. DUAL SPACING	239 mm
PATTERN DEPTH	13.4 mm

EU-LABEL VALUES

ROLLING RESISTANCE	D
WET GRIP	D
NOISE	72 dB
NOISE WAVES	A
MARKINGS	M+S, SnowGrip, Traction, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

Tyre have been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/