

## 235/75R17.5 132/130M NOKIAN E-TRUCK STEER

A sturdy steer axle tire for regional and urban traffic

PRODUCT CODE	T675253
APPLICATION	Steer
LI / SPEED SYMBOL	132/130M
RIM RECOMMENDED	6.75
RIM PERMITTED	7.50
TYPE APPROVAL	E4 0046218, E4 0210252 S2WR2



### LOAD CAPACITY, KG

Axle fitting	Speed (km/h)	Pressure (kPa)									
		550	575	600	625	650	675	700	725	750	775
Single	130	3040	3150	3260	3370	3470	3580	3690	3790	3900	4000
Dual	130	5780	5990	6190	6400	6600	6800	7010	7210	7400	7600

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

### TIRE DIMENSIONS

OVERALL DIAMETER	791 mm
TIRE WIDTH	238 mm
STATIC LOADED RADIUS	370 mm
ROLLING CIRCUMFERENCE	2404 mm
MIN. DUAL SPACING	262 mm
PATTERN DEPTH	12.2 mm

### EU-LABEL VALUES

ROLLING RESISTANCE	C
WET GRIP	B
NOISE	67 dB
NOISE WAVES	A
MARKINGS	M+S, SnowGrip, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

Tyre have been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: [www.nokiantyres.com/heavy/technical-tire-manual/](http://www.nokiantyres.com/heavy/technical-tire-manual/)