

265/70R19.5 140/138M NOKIAN TYRES E-TRUCK STEER

A sturdy steer axle tire for medium-sized trucks in regional and urban traffic

PRODUCT CODE	T675263
APPLICATION	Steer
LI / SPEED SYMBOL	140/138M
RIM RECOMMENDED	7.50
RIM PERMITTED	6.75, 8.25
TYPE APPROVAL	E4 0043517, E4 0210252 S2WR2



LOAD CAPACITY, KG

Axle fitting	Speed (km/h)	Pressure (kPa)									
		550	575	600	625	650	675	700	725	750	775
Dual	130	7170	7430	7690	7950	8200	8450	8700	8950	9200	9440
Single	130	3800	3940	4070	4210	4340	4480	4610	4740	4870	5000

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

TIRE DIMENSIONS

OVERALL DIAMETER	859 mm
TIRE WIDTH	252 mm
STATIC LOADED RADIUS	398 mm
ROLLING CIRCUMFERENCE	2611 mm
MIN. DUAL SPACING	295 mm
PATTERN DEPTH	12.7 mm

EU-LABEL VALUES

ROLLING RESISTANCE	C
WET GRIP	B
NOISE	68 dB
NOISE WAVES	A
MARKINGS	M+S, SnowGrip, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

Tyre have been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/