

## 285/70R19.5 145/143M NOKIAN TYRES E-TRUCK STEER

A sturdy steer axle tire for medium-sized trucks in regional and urban traffic

PRODUCT CODE	T675262
APPLICATION	Steer
LI / SPEED SYMBOL	145/143M
RIM RECOMMENDED	8.25
RIM PERMITTED	9.00
TYPE APPROVAL	E4 0043516, E4 0210252 S2WR2



### LOAD CAPACITY, LB

Axle fitting	Speed (mph)	Pressure (psi)										
		87	91	94	98	102	105	109	112	116	120	123
Dual	80	18190	18785	19380	19975	20570	21165	21740	22310	22885	23455	24030
Single	80	9680	10010	10320	10625	10955	11265	11575	11885	12190	12480	12785

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

### TIRE DIMENSIONS

OVERALL DIAMETER	34.9 in
TIRE WIDTH	10.6 in
STATIC LOADED RADIUS	16.1 in
ROLLING CIRCUMFERENCE	106.1 in
MIN. DUAL SPACING	12.5 in
PATTERN DEPTH	17/32 in

### EU-LABEL VALUES

ROLLING RESISTANCE	C
WET GRIP	C
NOISE	67 dB
NOISE WAVES	A
MARKINGS	M+S, SnowGrip, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

Tyre have been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: [www.nokiantyres.com/heavy/technical-tire-manual/](http://www.nokiantyres.com/heavy/technical-tire-manual/)