

## 385/55R22.5 160K NOKIAN E-TRUCK STEER

### Steady handling in the long run

PRODUCT CODE	T675248
APPLICATION	Steer
LI / SPEED SYMBOL	160K
RIM RECOMMENDED	11.75
RIM PERMITTED	12.25
TYPE APPROVAL	E4 0046223, E4 0210252 S2WR2



### LOAD CAPACITY, KG

Axle fitting	Speed (km/h)	Pressure (kPa)										
		650	675	700	725	750	775	800	825	850	875	900
Single	110	6940	7150	7360	7570	7780	7990	8190	8390	8600	8800	9000

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

### TIRE DIMENSIONS

OVERALL DIAMETER	999 mm
TIRE WIDTH	381 mm
STATIC LOADED RADIUS	465 mm
ROLLING CIRCUMFERENCE	3037 mm
PATTERN DEPTH	12.5 mm

### EU-LABEL VALUES

ROLLING RESISTANCE	B
WET GRIP	B
NOISE	68 dB
NOISE WAVES	A
MARKINGS	M+S, SnowGrip, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

Tyre have been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: [www.nokiantyres.com/heavy/technical-tire-manual/](http://www.nokiantyres.com/heavy/technical-tire-manual/)