

215/75R17.5 135/133J NOKIAN TYRES E-TRUCK TRAILER

Reliable all-season tires for long and medium haul

PRODUCT CODE	T675254
APPLICATION	Trailer
LI / SPEED SYMBOL	135/133J
RIM RECOMMENDED	6.00
RIM PERMITTED	6.75
TYPE APPROVAL	E4 0043502, E4 028996 S2WR2



LOAD CAPACITY, KG

Axle fitting	Speed (km/h)	Pressure (kPa)								
		650	675	700	725	750	775	800	825	850
Dual	100	6650	6850	7050	7260	7450	7650	7850	8050	8240
Single	100	3520	3630	3730	3840	3940	4050	4150	4260	4360

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

TIRE DIMENSIONS

OVERALL DIAMETER	776 mm
TIRE WIDTH	212 mm
STATIC LOADED RADIUS	363 mm
ROLLING CIRCUMFERENCE	2359 mm
MIN. DUAL SPACING	239 mm
PATTERN DEPTH	12 mm

EU-LABEL VALUES

ROLLING RESISTANCE	D
WET GRIP	B
NOISE	69 dB
NOISE WAVES	A
MARKINGS	M+S, SnowGrip, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

Tyre have been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/