

245/70R17.5 143/141J NOKIAN TYRES E-TRUCK TRAILER

Reliable all-season tires for long and medium haul

PRODUCT CODE	T675246
APPLICATION	Trailer
LI / SPEED SYMBOL	143/141J (146/146F)
RIM RECOMMENDED	6.75
TYPE APPROVAL	E4 0043096, E4 028996 S2WR2



LOAD CAPACITY, LB

Axle fitting	Speed (mph)	Pressure (psi)									
		94	98	102	105	109	112	116	120	123	127
Dual	62.5	17900	18455	19005	19535	20060	20615	21140	21670	22180	22710
Single	62.5	9480	9765	10055	10340	10625	10915	11175	11465	11750	12015

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

TIRE DIMENSIONS

OVERALL DIAMETER	31.4 in
TIRE WIDTH	9.6 in
STATIC LOADED RADIUS	14.5 in
ROLLING CIRCUMFERENCE	95.4 in
MIN. DUAL SPACING	11 in
PATTERN DEPTH	16/32 in

EU-LABEL VALUES

ROLLING RESISTANCE	D
WET GRIP	A
NOISE	71 dB
NOISE WAVES	A
MARKINGS	M+S, SnowGrip, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

Tyre have been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/