

295/60R22.5 150/147L NOKIAN HAKKA TRUCK DRIVE

Grip around the year

PRODUCT CODE	T675250
APPLICATION	Drive
LI / SPEED SYMBOL	150/147L
RIM RECOMMENDED	9.00
RIM PERMITTED	9.75
TYPE APPROVAL	E4 0044473, E4 0211773 S2WR2



LOAD CAPACITY, LB

Axle fitting	Speed (mph)	Pressure (psi)										
		94	98	102	105	109	112	116	120	123	127	131
Single	75	11375	11730	12080	12435	12765	13095	13450	13780	14110	14440	14770
Dual	75	20900	21540	22180	22820	23435	24050	24670	25285	25905	26520	27115

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

TIRE DIMENSIONS

OVERALL DIAMETER	36.7 in
TIRE WIDTH	11.8 in
STATIC LOADED RADIUS	17.2 in
ROLLING CIRCUMFERENCE	111.4 in
MIN. DUAL SPACING	13 in
PATTERN DEPTH	19/32 in

EU-LABEL VALUES

ROLLING RESISTANCE	D
WET GRIP	C
NOISE	76 dB
NOISE WAVES	B
MARKINGS	M+S, SnowGrip, Traction, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according to the ETRTO and TRA standards.

Tyre have been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/