

## 295/80R22.5 152/148M NOKIAN HAKKA TRUCK DRIVE

### Grip around the year

PRODUCT CODE	T675034
APPLICATION	Drive
LI / SPEED SYMBOL	152/148M
RIM RECOMMENDED	9.00
RIM PERMITTED	8.25
TYPE APPROVAL	E4 0034417, E4 0211773 S2WR2



### LOAD CAPACITY, LB

Axle fitting	Speed (mph)	Pressure (psi)								
		94	98	102	105	109	112	116	120	123
Dual	80	22420	23105	23790	24450	25135	25795	26455	27115	27780
Single	80	12630	13005	13405	13780	14155	14530	14905	15280	15655

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

### TIRE DIMENSIONS

OVERALL DIAMETER	41.7 in
TIRE WIDTH	11.7 in
STATIC LOADED RADIUS	19.2 in
ROLLING CIRCUMFERENCE	126.9 in
MIN. DUAL SPACING	13.2 in
PATTERN DEPTH	23/32 in

### EU-LABEL VALUES

ROLLING RESISTANCE	E
WET GRIP	C
NOISE	75 dB
NOISE WAVES	B
MARKINGS	M+S, SnowGrip, Traction, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according to the ETRTO and TRA standards.

Tyre have been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: [www.nokiantyres.com/heavy/technical-tire-manual/](http://www.nokiantyres.com/heavy/technical-tire-manual/)