

315/60R22.5 154/148L NOKIAN HAKKA TRUCK STEER

Stable steering tire for all seasons

PRODUCT CODE	T675249
APPLICATION	Steer
LI / SPEED SYMBOL	154/149L
RIM RECOMMENDED	9.00
RIM PERMITTED	9.75
TYPE APPROVAL	E4 0044466, E4 028997 S2WR2



LOAD CAPACITY, LB

Axle fitting	Speed (mph)	Pressure (psi)										
		94	98	102	105	109	112	116	120	123	127	131
Dual	75	22090	22775	23435	24120	24780	25420	26080	26740	27380	28020	28660
Single	75	12745	13140	13515	13910	14285	14660	15060	15430	15785	16160	16535

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

TIRE DIMENSIONS

OVERALL DIAMETER	37.8 in
TIRE WIDTH	12.4 in
STATIC LOADED RADIUS	17.7 in
ROLLING CIRCUMFERENCE	114.8 in
MIN. DUAL SPACING	13.5 in
PATTERN DEPTH	16/32 in

EU-LABEL VALUES

ROLLING RESISTANCE	C
WET GRIP	B
NOISE	72 dB
NOISE WAVES	B
MARKINGS	M+S, SnowGrip, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according to the ETRTO and TRA standards.

Tyre have been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/