

295/80R22.5 152/148J NOKIAN TYRES HAKKAPELIITTA CITY BUS

Durability and winter grip for city buses

PRODUCT CODE	T675240
APPLICATION	Steer / Drive
LI / SPEED SYMBOL	152/148J (154/150E)
RIM RECOMMENDED	9.00
RIM PERMITTED	8.25
TYPE APPROVAL	E4 0041616, E4 029083 S2WR2



LOAD CAPACITY, KG

Axle fitting	Speed (km/h)	Pressure (kPa)								
		650	675	700	725	750	775	800	825	850
Single	100	5730	5900	6080	6250	6420	6590	6760	6930	7100
Dual	100	10170	10480	10790	11090	11400	11700	12000	12300	12600

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

TIRE DIMENSIONS

OVERALL DIAMETER	1044 mm
TIRE WIDTH	298 mm
STATIC LOADED RADIUS	491 mm
ROLLING CIRCUMFERENCE	3204 mm
MIN. DUAL SPACING	335 mm
PATTERN DEPTH	17 mm

EU-LABEL VALUES

ROLLING RESISTANCE	D
WET GRIP	B
NOISE	75 dB
NOISE WAVES	B
MARKINGS	M+S, SnowGrip, Traction, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

Tyre have been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/