

# 315/70R22.5 154/150L NOKIAN TYRES HAKKAPELIITTA TRUCK E2

PRODUCT CODE	T675258
APPLICATION	Drive
LI / SPEED SYMBOL	154/150L (152/148M)
RIM RECOMMENDED	9.00
RIM PERMITTED	8.25
TYPE APPROVAL	E4 0045766, E4 0211471 S2WR2



## LOAD CAPACITY, LB

Axle fitting	Speed (mph)	Pressure (psi)								
		94	98	102	105	109	112	116	120	123
Dual	75	23830	24560	25285	26015	26720	27450	28155	28835	29540
Single	75	13340	13755	14155	14550	14970	15365	15740	16140	16535

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

## TIRE DIMENSIONS

OVERALL DIAMETER	40.4 in
TIRE WIDTH	12.4 in
STATIC LOADED RADIUS	18.7 in
ROLLING CIRCUMFERENCE	122.9 in
MIN. DUAL SPACING	13.8 in
PATTERN DEPTH	23/32 in

## EU-LABEL VALUES

ROLLING RESISTANCE	D
WET GRIP	D
NOISE	74 dB
NOISE WAVES	B
STUDDABLE	Marked stud positions on tread Number of studs 162 pcs Recommended stud 11-15
MARKINGS	M+S, SnowGrip, Traction, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

Tyre have been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: [www.nokiantyres.com/heavy/technical-tire-manual/](http://www.nokiantyres.com/heavy/technical-tire-manual/)