

315/80R22.5 156/150L NOKIAN HKPL TRUCK F2

Steering axle tire for demanding winter conditions

PRODUCT CODE	T675039
APPLICATION	Steer
LI / SPEED SYMBOL	156/150L (154/150M)
RIM RECOMMENDED	9.00
RIM PERMITTED	9.75
TYPE APPROVAL	E4 0034418, E4 027963 S2WR2



LOAD CAPACITY, LB

Axle fitting	Speed (mph)	Pressure (psi)								
		94	98	102	105	109	112	116	120	123
Dual	75	24405	25155	25905	26630	27380	28110	28815	29540	
Single	75	14220	14660	15100	15520	15960	16380	16800	17220	17635

Axle fitting	Speed (mph)	Pressure (psi)							
		94	98	102	105	109	112	116	120
Single	80	13670	14090	14505	14905	15320	15720	16140	16535
Dual	80	24405	25155	25905	26630	27380	28110	28815	29540

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

TIRE DIMENSIONS

OVERALL DIAMETER	42.4 in
TIRE WIDTH	12.3 in
STATIC LOADED RADIUS	19.7 in
ROLLING CIRCUMFERENCE	129 in
MIN. DUAL SPACING	13.8 in
PATTERN DEPTH	20/32 in

EU-LABEL VALUES

ROLLING RESISTANCE	D
WET GRIP	B
NOISE	73 dB
NOISE WAVES	B
STUDDABLE	Marked stud positions on tread Number of studs 160 pcs Recommended stud 11-15
MARKINGS	M+S, SnowGrip, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

Tyre have been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/