

385/65R22.5 164K NOKIAN TYRES HAKKAPELIITTA TRUCK F2 XL

Steering axle tire for demanding winter conditions

PRODUCT CODE	T675237
APPLICATION	Steer / Trailer
LI / SPEED SYMBOL	164K
RIM RECOMMENDED	11.75
RIM PERMITTED	12.25
TYPE APPROVAL	E4 0041799, E4 0210618 S2WR2



LOAD CAPACITY, LB

Axle fitting	Speed (mph)	Pressure (psi)										
		94	98	102	105	109	112	116	120	123	127	131
Single	67.5	17000	17505	18035	18540	19050	19555	20060	20570	21055	21560	22045

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

TIRE DIMENSIONS

OVERALL DIAMETER	42.7 in
TIRE WIDTH	15 in
STATIC LOADED RADIUS	19.7 in
ROLLING CIRCUMFERENCE	129.7 in
PATTERN DEPTH	20/32 in

EU-LABEL VALUES

ROLLING RESISTANCE	C
WET GRIP	B
NOISE	75 dB
NOISE WAVES	B
STUDDABLE	Marked stud positions on tread Number of studs 142 pcs Recommended stud 11-15
MARKINGS	M+S, SnowGrip, Traction, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

Tyre have been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/