

# 315/80R22.5 156/150K NOKIAN TYRES R-TRUCK STEER

For controlled steering both on and off-road

PRODUCT CODE	T675238
APPLICATION	Steer
LI / SPEED SYMBOL	156/150K
RIM RECOMMENDED	9.00
RIM PERMITTED	9.75
TYPE APPROVAL	E4 0041613, E4 0210404 S2WR2



## LOAD CAPACITY, LB

Axle fitting	Speed (mph)	Pressure (psi)							
		94	98	102	105	109	112	116	120
Dual	67.5	24405	25155	25905	26630	27380	28110	28815	29540
Single	67.5	14575	15015	15455	15895	16335	16775	17220	17635

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

## TIRE DIMENSIONS

OVERALL DIAMETER	42.6 in
TIRE WIDTH	12.2 in
STATIC LOADED RADIUS	19.8 in
ROLLING CIRCUMFERENCE	129.5 in
MIN. DUAL SPACING	13.8 in
PATTERN DEPTH	20/32 in

## EU-LABEL VALUES

ROLLING RESISTANCE	C
WET GRIP	B
NOISE	70 dB
NOISE WAVES	A
MARKINGS	M+S, SnowGrip, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

Tyre have been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: [www.nokiantyres.com/heavy/technical-tire-manual/](http://www.nokiantyres.com/heavy/technical-tire-manual/)