

ALTERNATIVE SIZE TABLE FOR PASSENGER CARS

Size	60 series	55 series	50 series	45 series	40 series	35/30 series
185/65 R 15	205/60 R 15	195/55 R 16		215/45 R 17	235/40 R 17	
	195/60 R 15			205/45 R 17	245/40 R 17	
195/65 R 15	215/60 R 15	205/55 R 16	205/50 R 17	225/45 R 17	255/40 R 17	255/35 R 18
	195/60 R 16	215/55 R 16	225/50 R 16	235/45 R 17	225/40 R 18	265/35 R 18
	205/60 R 15			215/45 R 17	245/40 R 17	
205/65 R 15	205/60 R 16	215/55 R 16	205/50 R 17	235/45 R 17	235/40 R 18	235/35 R 19
	195/60 R 16	225/55 R 16	215/50 R 17		245/40 R 18	225/35 R 19
	215/60 R 15		225/50 R 17			265/35 R 18
215/65 R 15	215/60 R 16	225/55 R 16	225/50 R 17	245/45 R 17	255/40 R 18	255/35 R 19
	225/60 R 15	215/55 R 17	235/50 R 17	225/45 R 18	245/40 R 18	295/30 R 18
	205/60 R 16					245/35 R 19
205/55 R 16	205/60 R 15	205/55 R 16	225/50 R 16	215/45 R 17	255/40 R 17	255/35 R 18
	195/60 R 16		205/50 R 17	225/45 R 17	245/40 R 18	225/35 R 19
					225/40 R 18	285/30 R 18
215/55 R 16	195/60 R 16	215/55 R 16	215/50 R 17	235/45 R 17	235/40 R 18	265/35 R 18
	205/60 R 16		205/50 R 17	225/45 R 17	225/40 R 18	225/35 R 19
				245/45 R 17	255/40 R 17	235/35 R 19
225/55 R 16	205/60 R 16	225/55 R 16	225/50 R 17	245/45 R 17	245/40 R 18	245/35 R 19
	225/60 R 15		215/50 R 17	225/45 R 18	235/40 R 18	235/30 R 19
						255/35 R 19

The enclosed table presents a breakdown of alternative sizes with a rolling circumference of $\pm 1.5\%$ when compared with the size on the left.

When using an alternative size, remember to check the following:

- The load capacity of the tyre is sufficient for the axle loads of the vehicle.
- The rim is the right size and the offset has been approved by the car manufacturer.
- The wheel can work correctly on the car under all conditions.

The vehicle modification must be officially inspected if:

- The nominal diameter differs from the original by more than 26 mm
- The width of the tyre differs from the original by more than 30 mm