

# nokian<sup>®</sup> TYRES

## WR C3 COMMERCIAL PERFORMANCE IN ALL WEATHER CONDITIONS

±45°F ±7°C

ALL-WEATHER  
CONDITIONS



VAN / CARGO

### ARAMID SIDEWALLS

The Aramid sidewalls offer durability and protection for surprising situations. The sidewall compound is exceptionally durable and puncture-resistant thanks to extremely strong aramid fibers. It's the same material utilized by the aerospace and defense industries. Aramid fiber strengthens the sidewall rubber to withstand external impacts and pressing against the wheel flange.

### PUMP SIPES

Pocket-shaped pump sipes on the tread blocks of the tire's outer edges ensure good contact with the driving surface. Sipes, the cuts on the tire tread, pump water off the road's surface, ensuring that the tire maintains good contact with the driving surface.

### SPECIAL CLINCH RUBBER COMPOUND

The compound presses flexibly against the foot of the rim, making the bead area more durable when handling massive loads. This innovation also successfully minimizes cabin noise, since it reduces vibrations from the tire body, preventing them from passing onto the rim and inside the vehicle.

- COMMERCIAL CONSTRUCTION
- POLISHED GROOVES
- SEVERE SERVICE EMBLEM
- WINTER SAFETY INDICATOR (WSI)
- LOW ROLLING RESISTANCE



\*The Nokian Tyres 30-Day Satisfaction Guarantee and Nokian Tyres' Pothole Protection excludes tires used in commercial applications.



14-17  
inches



R-106 m/h • 170 km/h  
S-112 m/h • 180 km/h  
T-118 m/h • 190 km/h



VISIT [NOKIANTIRES.COM](https://www.nokiantires.com)



## NOKIAN TYRES WR C3 • ALL-WEATHER TIRE

VAN/CARGO • ARAMID STRONG SIDEWALLS



RIM	SIZE/SPEED RATING	PRODUCT CODE	WEIGHT LBS.	RIM WIDTH		OVERALL DIAMETER	OVERALL WIDTH	TREAD DEPTH 32ND	REVOLUTIONS PER		LOAD RANGE
				APPROVED	MEASURING				MILE	KM	
15	205/65 R 15 C 102/100 T	T429136	25.4	5.5-6.5	6.0	25.5	8.2	12	813	505	C
	185/60 R 15 C 94/92 T	T429939	16.5	5.5-6	5.5	23.7	7.4	12	877	545	C
16	195/75 R 16 C 107/105 S	T429127	26.8	5-6	5.5	27.5	7.7	12	758	471	D
	225/75 R 16 C 121/120 R	T429130	34.1	6-7	6.0	29.3	8.8	12	710	441	E
	235/65 R 16 C 121/119 R	T429142	34.4	6.5-7.5	7.0	28.0	9.4	12	741	461	E

\*The Nokian Tyres 30-Day Satisfaction Guarantee and Nokian Tyres' Pothole Protection excludes tires used in commercial applications.

### NOTE:



**C** = Commercial (Example: 235/65 R 16 **C**) Euro-metric tire sizes ending with a **C** are commercial tires, for use on delivery trucks and vans capable of carrying heavy loads. In addition to the **C** designation, these sizes are also branded with a load range and service description rating (**load range C, D or E**).



The sidewall is reinforced with extremely strong aramid fibers for impact resistance.

GREEN AREA INDICATES WHERE THE ARAMID FIBERS HAVE BEEN ADDED.