

nokian[®] TYRES

NEW

OUTPOST nAT

EXTEND YOUR ADVENTURES



ALL-WEATHER
CONDITIONS

LIGHT TRUCK / SUV / VAN / CARGO

EXTEND YOUR TERRAIN

The Nokian Tyres Outpost nAT helps drivers remove their limits and confidently go wherever their journeys demand.

- SUMMIT SIDEWALLS
- CANYON CUTS
- SHOULDER NOTCHES

EXTEND YOUR TOUGHNESS

The Nokian Tyres Outpost nAT is stocked with technology to protect drivers in the most rugged environments.

- POTHOLE PROTECTION
- ARAMID SHIELD TECHNOLOGY
- GRAVEL GUARDS
- HIGH LOAD CAPACITY

EXTEND YOUR TRAVEL

The Nokian Tyres Outpost nAT offers high mileage thanks to a tailored tread whose landscape is forged with protective features.

- TRIPLE PITCH DESIGN
- DURABLE TREAD COMPOUND
- TREAD BLOCK BRIDGING & SLOPE SUPPORTS
- DRIVING SAFETY INDICATOR (DSI)

UPDATES INCLUDE:

- NOW MADE IN USA
- MORE AGGRESSIVE SIDEWALL DESIGN
- RAISED LETTERING AND SMOOTH SIDEWALLS
- SQUARER TREAD PROFILE
- REDESIGNED TREAD SUPPORTS, FOR MORE AGGRESSIVE LOOK



UTQG: 700 A/A P-Metric sizes
P-Metric sizes: 60,000 Mile / 100 000 km Limited Treadwear Warranty
LT sizes: 60,000 Mile / 100 000 km Limited Treadwear Warranty*
The Nokian Tyres 30-Day Satisfaction Guarantee and Nokian Tyres Pothole Protection excludes tires used in commercial applications.



M + S



15-22
inches



R-106 m/h • 170 km/h
S-112 m/h • 180 km/h
T-118 m/h • 190 km/h
H-130 m/h • 210 km/h



P-METRIC • ARAMID TOUGH SHIELD • UTQG RATING: 700/A/A • 60,000 MILE / 100 000 KM LIMITED TREADWEAR WARRANTY*



Rim	Size/Speed Rating	Product Code	Weight (lbs)	Rim Width		Overall Diameter	Overall Depth	Tread Depth (32nd)	Revolutions Per	
				Approved	Measuring				Mile	Km
15	235/75 R 15 109T XL	T432846	33.1	6-8	6.5	28.9	9.3	14	720	447
16	245/75 R 16 111T	T432848	37.5	6.5-8	7.0	30.5	9.8	14	681	423
	265/75 R 16 116T	T432847	43.0	7-9	7.5	31.6	10.5	14	659	410
	235/70 R 16 109T XL	T432892	34.2	6-8	7.0	29.0	9.4	14	715	444
	245/70 R 16 111T XL	T432862	36.4	6.5-8	7.0	29.5	9.8	14	706	438
	255/70 R 16 111T	T432893	38.6	6.5-8.5	7.5	30.1	10.2	14	691	429
	265/70 R 16 112T	T432849	40.8	7-9	8.0	30.6	10.7	14	681	423
17	235/75 R 17 109S	T432850	37.5	6-8	6.5	30.9	9.3	14	673	418
	255/75 R 17 115S	T432894	43.0	6.5-8.5	7.0	32.0	10.0	14	651	404
	245/70 R 17 110T	T432853	37.5	6.5-8	7.0	30.5	9.8	14	681	423
	255/70 R 17 112T	T432851	39.7	6.5-8.5	7.5	31.1	10.2	14	668	415
	265/70 R 17 115T	T432852	43.0	7-9	8.0	31.6	10.7	14	659	410
	285/70 R 17 116T	T432854	46.3	7.5-9.5	8.5	32.8	11.5	14	634	394
	235/65 R 17 108T XL	T432895	35.3	6.5-8.5	7.0	29.1	9.4	14	715	444
	245/65 R 17 111T XL	T432855	36.4	7-8.5	7.0	29.5	9.8	14	706	438
	255/65 R 17 110T	T432856	39.7	7-9	7.5	30.1	10.2	14	691	429
	265/65 R 17 116T XL	T432857	41.9	7.5-9.5	8.0	30.5	10.7	14	681	423
18	255/70 R 18 116H XL	T432858	43.0	6.5-8.5	7.5	32.1	10.2	14	647	402
	265/70 R 18 116S	T432859	45.2	7-9	8.0	32.6	10.7	14	638	396
	265/65 R 18 114H	T432841	41.9	8.5-9.5	8.0	31.5	10.7	14	659	410
	275/65 R 18 116T	T432842	45.2	7.5-9.5	8.0	32.1	11.0	14	647	402
	255/60 R 18 112H XL	T432896	38.6	7-9	7.5	30.0	10.2	14	691	429
	265/60 R 18 114T XL	T432843	40.8	7-9.5	8.0	30.5	10.7	14	681	423
20	275/60 R 20 115H	T432845	46.3	7.5-9.5	8.0	33.0	11.0	14	630	392
	275/55 R 20 117T XL	T432844	45.2	7.5-9.5	8.5	31.9	11.2	14	651	404
22	285/45 R 22 114H XL	T432840	43.0	9-10.5	9.5	32.1	11.2	14	647	402

LT-METRIC • ARAMID TOUGH SHIELD • 60,000 MILE / 100 000 KM LIMITED TREADWEAR WARRANTY*



Rim	Size/Speed Rating	Product Code	Weight (lbs)	Rim Width		Overall Diameter	Overall Depth	Tread Depth (32nd)	Revolutions Per		Load Range / Ply Rating
				Approved	Measuring				Mile	Km	
15	LT235/75 R 15 116/113S	T432867	39.7	6-7	6.5	28.9	9.3	18	720	447	E (10)
	31x10.50 R 15 LT 109S	T432868	46.3	7-9	8.5	30.5	10.5	18	681	423	C (6)
16	LT215/85 R 16 115/112S	T432869	44.1	5.5-7	6.0	30.4	8.5	18.0	686	426	E (10)
	LT235/85 R 16 120/116S	T432870	45.2	6-7.5	6.5	31.7	9.3	18.0	655	407	E (10)
	LT225/75 R 16 115/112S	T432871	40.8	6-7	6.0	29.3	8.8	18.0	710	441	E (10)
	LT245/75 R 16 120/116S	T432863	46.3	6.5-8	7.0	30.5	9.8	18.0	681	423	E (10)
	LT265/75 R 16 123/120S	T432865	49.6	7-8	7.5	31.6	10.5	18.0	659	410	E (10)
	LT285/75 R 16 126/123S	T432866	52.9	7.5-9	8.0	32.8	11.3	18.0	634	394	E (10)
17	LT235/80 R 17 120/117S	T432882	45.2	6-7.5	6.5	31.8	9.3	18.0	655	407	E (10)
	LT245/75 R 17 121/118S	T432864	48.5	6.5-7.5	7.0	31.5	9.8	18.0	659	410	E (10)
	LT285/75 R 17 128/125S	T432861	55.1	7.5-9.5	8.0	33.9	11.3	18.0	615	382	E (10)
	LT245/70 R 17 119/116S	T432877	47.4	6.5-8	7.0	30.5	9.8	18.0	681	423	E (10)
	LT265/70 R 17 123/120S	T432878	50.7	7-8.5	8.0	31.6	10.7	18.0	659	410	E (10)
	LT275/70 R 17 124/121S	T432879	50.7	7-8.5	8.0	32.2	11.0	18.0	647	402	E (10)
	LT285/70 R 17 126/123S	T432875	54.0	7.5-9	8.5	32.8	11.5	18.0	634	394	E (10)
	LT315/70 R 17 128/125S	T432876	60.6	8-11	9.5	34.4	12.7	18.0	604	375	F (12)
	35x12.50 R 17 LT 128R	T432838	61.7	8.5-11	10.0	34.5	12.5	18.0	604	375	F (12)
	LT285/75 R 18 129/126S	T432837	58.4	7.5-9.5	8.0	34.8	11.3	18.0	597	371	E (10)
18	LT265/70 R 18 124/121S	T432872	52.9	7-9	8.0	32.6	10.7	18.0	638	396	E (10)
	LT275/70 R 18 125/122S	T432873	55.1	7-8.5	8.0	33.2	11.0	18.0	626	389	E (10)
	LT295/70 R 18 129/126S	T432874	58.4	7.5-10	8.5	34.3	11.8	18.0	607	377	E (10)
	LT275/65 R 18 123/120S	T432890	52.9	7.5-9	8.0	32.1	11.0	18.0	647	402	E (10)
	LT285/65 R 18 125/122S	T432891	54.0	8-10	8.5	32.6	11.5	18.0	638	396	E (10)
	35x12.50 R 18 LT 128R	T432887	61.7	8.5-11	10.0	34.5	12.5	18.0	604	375	F (12)
20	LT275/65 R 20 126/123S	T432888	57.3	7.5-9.5	8.0	34.1	11.0	18.0	611	380	E (10)
	LT285/65 R 20 127/124S	T432860	58.4	8-10	8.5	34.6	11.5	18.0	600	373	E (10)
	LT265/60 R 20 121/118S	T432889	52.9	7.5-9.5	8.0	32.5	10.7	18.0	638	396	E (10)
	LT275/60 R 20 123/120S	T432880	55.1	7.5-9.5	8.0	33.0	11.0	18.0	630	392	E (10)
	LT285/60 R 20 125/122S	T432881	57.3	8-10	8.5	33.5	11.5	18.0	622	387	E (10)
	LT295/60 R 20 126/123S	T432839	58.4	8-10	8.5	33.9	11.8	18.0	615	382	E (10)
	LT275/55 R 20 120/117S	T432884	52.9	7.5-9.5	8.5	31.9	11.2	18.0	651	404	E (10)
	LT285/55 R 20 122/119S	T432885	55.1	8-10	9.0	32.4	11.7	18.0	643	399	E (10)
	LT305/55 R 20 125/122S	T432886	56.2	8.5-11	9.5	33.2	12.4	18.0	626	389	E (10)
	35x12.50 R 20 LT 125R	T432883	62.8	8.5-11	10.0	34.5	12.5	18.0	604	375	E (10)