



**nokian<sup>®</sup>**  
**TYRES**

# Nokian Forest King F2

Heavy loads, muddy soil and the gnarly, unforgiving forest. These are the conditions Nokian Forest King F2 thrives on. High puncture resistance, new pattern design for track use and excellent sidewall protection ensures that you can fill your load to the brim and keep going.



# Track grip like never before

Technical data							
Product	710/40-24.5	600/55-26.5	710/45-26.5	710/45-26.5	750/55-26.5	710/55-28.5	780/50-28.5
PR	20	20	20	24	24	24	24
Product number	T445572	T445573	T445571	T445589	T445574	T445570	T445537
LI/SS	163 A8 / 170 A2	165 A8 / 172 A2	168 A8 / 173 A2	173 A8 / 180 A2	182 A8 / 189 A2	180 A8 / 187 A2	182 A8 / 190 A2
Width / mm	710	600	710	710	750	710	780
Diameter / mm	1230	1340	1340	1340	1485	1525	1525
Rim recommended	AG 24.00	AG 20.00	AG 24.00	AG 24.00	AG 24.00	AG 24.00	AG 26.00
Max inflation pressure	550 kPa	550 kPa	550 kPa	600 kPa	600 kPa	600 kPa	600 kPa

Load carrying capacity	500 kPa	500 kPa	500 kPa	600 kPa	600 kPa	600 kPa	600 kPa
30 km/h Road service	5220 kg	5510 kg	5990 kg	6960 kg	9100 kg	8560 kg	9100 kg
20 km/h Road service	6000 kg	6330 kg	6890 kg	8000 kg	10460 kg	9840 kg	10460 kg
10 km/h Forestry service / LT	6000 kg	6300 kg	6900 kg	8000 kg	10000 kg	9759 kg	10600 kg

Tube product code	T545448	T55098	T55099	T55099	T55102	T545543	T545543
Tube valve	TR 218A	TR 218A	TR 218A	TR 218A	TR 218A	TR 218A	TR 218A
Tyre available	Q3 / 2014	Q4 / 2014	Available	Available	Q3 / 2014	Available	Available



**Totally new size 28.5" introduced for heavy weight forestry machinery**

- Max capacity 10600kg/600kPa

**New tread pattern for perfect track support**

- 6% more rubber at tread surface compared to Forest King F for better puncture resistance
- Reduced stress on bogies and tyres

**Wider tread bar at shoulder for more support to tracks**

**New straight section in the rib for better track support**

- Track cross bar stays straight

**Special compound at bead area**

- Higher resistance against rim slip

**Designed for maximum track grip**

- Every third(fourth) track cross bar fits to tread grooves