

A close-up, low-angle shot of a large, treaded tractor tire. The tire is dark and appears to be on a red tractor, with a red metal lattice visible in the background. The tire's tread is deeply grooved and siped, designed for off-road use. The background shows a dense forest of tall, thin trees under a bright sky, with sunlight filtering through the canopy, creating a hazy, atmospheric effect. The overall scene is set in a forest, emphasizing the product's intended use.

nokian[®]
TYRES

Nokian Forest King TRS 2

Excellent traction in most demanding forestry use

NOKIAN FOREST KING TRS 2

New benchmark in traction

Those in the lead make their own roads, like Nokian Forest King TRS 2. The new, robust lug design ensures a precise lateral grip and powers a determined drive through even the most demanding of forests.



FEATURES FOR THE FOREST

- Wide tread for low ground pressure and excellent traction
- Proven very good self-cleaning
- New shoulder design gives excellent lateral grip
- Square tyre shape enables very good fitment of tracks
- High groove bottom on the shoulder gives added support to the track paws and greater puncture resistance
- New Super Shovel lug design provides superior traction
- Steel fortification against punctures



SIZE	LI/SS	PR	RIM	WIDTH	DIAMETER	LOADED STATIC RADIUS	ROLLING CIRCUM-FERENCE	LOAD CAPACITY			MAXIMUM INFLATION PRESSURE	PRODUCT CODE
								kg	kg	kg		
				mm	mm	mm	mm	10 km/h	30 km/h	40 km/h	kPa	
600/50-22.5	159 A8 / 167 A2	20	AG 20.00	600	1170	533	3550	5450	4680	4375	550	T445618
710/40-22.5	161 A8 / 168 A2	20	AG 24.00	710	1170	535	3569	5600	4950	4625	550	T445607
600/50-24.5	164 A8 / 171 A2	20	AG 20.00, AG 22.00*	600	1230	566	3738	6150	6150	5000	550	T445639
710/40-24.5	163 A8 / 170 A2	20	AG 24.00	710	1230	570	3757	6000	5220	4875	550	T445568
600/55-26.5	165 A8 / 172 A2	20	AG 20.00	600	1340	619	4096	6300	5510	5150	550	T445567
710/45-26.5	168 A8 / 175 A2	20	AG 24.00	710	1340	618	4103	6900	5990	5600	550	T445566
710/45-26.5	173 A8 / 180 A2	24	AG 24.00	710	1340	617	4115	8000	6960	6500	600	T445640
800/40-26.5	170 A8 / 177 A2	20	AG 28.00	800	1340	619	4096	7300	6420	6000	500	T445594
750/55-26.5	182 A8 / 189 A2	24	AG 24.00	750	1485	674	4499	10000	9100	8500	600	T445602
710/55-28.5	180 A8 / 187 A2	24	AG 24.00	710	1525	693	4618	9750	8560	8000	600	T445612
780/50-28.5	182 A8 / 190 A2	24	AG 26.00	780	1525	691	4611	10600	9100	8500	600	T445581

All sizes are SF (STEEL FORTIFIED) and TT (TUBE-TYPE), to be fitted with tube

* Permitted rim

READ MORE nokiantyres.com/heavy