



nokian[®]
TYRES

Nokian Nordman Forest

Excellent replacement tyre for forestry machines

Value that is hard to beat

The Nokian Nordman Forest product line is based on our earlier premium models, proven in years of real-world use and offering excellent value for money. Same quality, same durable design – only the price is lower. For a replacement tyre, it's hard to beat the Nokian Nordman Forest series.



**NOKIAN NORDMAN
FOREST ELS L-2**



**NOKIAN NORDMAN
FOREST F**



**NOKIAN NORDMAN
FOREST TRS L-2**

The strong, reliable tyre that gives you the familiar Nokian quality. It is fully compatible with corresponding tracks, chains, tubes and rims of Forest King F, TRS L-2 and ELS L-2 models. That's why it is an economical replacement tyre for forestry machines.

- Sturdy rubber compound with excellent cut and puncture resistance
- High load-bearing capacity
- Strong, reliable tread structure for demanding conditions

TECHNICAL SPECIFICATIONS

Nokian Nordman Forest

SIZE	LI/SS	PR	TREAD PATTERN	RIM	WIDTH		DIAMETER		LOADED STATIC RADIUS		ROLLING CIRCUMFERENCE		MAXIMUM INFLATION PRESSURE		LOAD CAPACITY					PRODUCT CODE	
					mm	in	mm	in	mm	in	mm	in	kPa	psi	10 km/h	5 mph	30 km/h	20 mph	40 km/h		25 mph
600/50-22.5	149 A8 / 156 A2	16	ELS L-2	AG 20.00	600	23.6	1171	46.1	543	21.4	3544	139.5	400	58	4000	8820	3480	7670	3250	7165	T445623
710/40-22.5	151 A8 / 158 A2	16	F	AG 24.00	710	28	1171	46.1	538	21.2	3 544	139,5	400	58	4250	9370	3690	8135	3450	7605	T445625
710/40-24.5	163 A8 / 170 A2	20	F	AG 24.00	710	28.0	1230	48.4	573	22.6	3729	146.8	550	80	6000	13230	5220	11510	4875	10745	T445599
600/55-26.5	165 A8 / 172 A2	20	F	AG 20.00	600	23.6	1340	52.8	624	24.6	4065	160.0	550	80	6300	13890	5510	12145	5150	11355	T445598
710/45-26.5	168 A8 / 175 A2	20	F	AG 24.00	710	28.0	1340	52.8	622	24.5	4046	159.3	550	80	6900	15210	5990	13205	5600	12345	T445565
750/55-26.5	177 A8 / 184 A2	20	F	AG 24.00	750	29.5	1485	58.5	680	26.8	4467	175.9	550	80	9000	19840	7810	17220	7300	16095	T445597
600/50-22.5	149 A8 / 156 A2	16	TRS L-2	AG 20.00	600	23,6	1 171	46,1	545	21,5	3 544	139,5	400	58	4000	8820	3480	7670	3250	7165	T445622
710/40-22.5	151 A8 / 158 A2	16	TRS L-2	AG 24.00	710	28,0	1 171	46,1	539	21,2	3 537	139,3	400	58	4250	9370	3690	8135	3450	7605	T445624
600/55-26.5	165 A8 / 172 A2	20	TRS L-2	AG 20.00	600	23,6	1 340	52,8	616	24,3	4 065	160,0	550	80	6300	13890	5510	12145	5150	11355	T445527
710/45-26.5	168 A8 / 175 A2	20	TRS L-2	AG 24.00	710	28,0	1 340	52,8	608	23,9	4 077	160,5	550	80	6900	15210	5990	13205	5600	12345	T445541
750/55-26.5	177 A8 / 184 A2	20	TRS L-2	AG 24.00	750	29,5	1 485	58,5	672	26,5	4 461	175,6	550	80	9000	19840	7810	17220	7300	16095	T445528
600/65-34	163 A8 / 170 A2	20	TRS L-2	DW20B	600	23,6	1 644	64,7	755	29,7	4 964	195,4	360	52	4875	10745	5220	11510	6000	13230	T445475
700/55-34	166 A8 / 173 A2	20	TRS L-2	DW24B, DW23B*	700	27,6	1 640	64,6	751	29,6	4 938	194,4	360	52	5300	11685	5670	12500	6500	14330	T445476
700/70-34	173 A8 / 180 A2	20	TRS L-2	DW20B	700	27,6	1 844	72,6	840	33,1	5 542	218,2	360	52	6500	14330	6960	15345	8000	17635	T445596

All sizes are SF (STEEL FORTIFIED) and TT (TUBE-TYPE), to be fitted with tube

*Permitted rim

[READ MORE nokiantyres.com/heavy](https://www.nokiantyres.com/heavy)