

nokian[®]
TYRES



Nokian TRI 2

Reliable performance
all year round

Nokian TRI 2

APPLICATION

Versatile professional contracting tyre for year-round use

Nokian TRI 2 excels in wide variety of tasks. From job sites to highways, from snowy winters to hot tarmac; its high durability, excellent fuel economy and comfortable driving response even under heavy loads make it a reliable choice for versatile contracting work.



- Versatile, environmentally friendly special tyre for modern farming, earthmoving and municipal work
- Very high durability on paved surfaces, excellent fuel economy and driving properties
- Good grip, high load-bearing capacity and a pleasant driving response
- Stable and fast on the road, gentle on delicate green areas
- Dependable grip for accurate driving on snow and ice (M+S pattern)



**LOHNUNTERNEHMEN RICHTER
GBR / MR. JÜRGEN &
CHRISTIAN RICHTER**

Amelinghausen, Germany

NOKIAN TRI 2

Grip you can rely on

You cannot change the weather but you can prepare for the extreme conditions. Nokian TRI 2 is designed for getting the job done around the year, in any weather. Stable and durable Nokian TRI 2 offers comfortable driving response and endurance both on and off-road.



More operating hours on and off-road

The outcome of continuous research and development by Nokian Heavy Tyres, Nokian TRI 2 is your most economic choice for efficient hourly output. Numerous independent studies and Nokian Tyres' own tests speak an indisputable language about the superiority of Nokian TRI 2. The latest test results clearly indicate it is a first-rate choice for applications that demand both driving and field work.

Up to
3 times

the service life of competing products ¹

Up to
5 litres/h

lower fuel consumption in comparison with competing products ¹

Up to
50%

better traction on snow and ice than standard pattern tractor tyre ²

Up to
35%

better traction on icy surface with studs than without studs ²

Competitive and
EQUAL

in traction, fuel consumption and noise levels with standard pattern tractor tyre ³

Tested to be
ECO

choice for green areas. Lower ground pressure than standard tractor tyre ³

¹ - Source: Research "Increase in efficiency of road transport on the example of different types of tires of tractors" (Prof. Yves Reckleben, Niels Schäfer and Michael Weißbach, Landtechnik, 68 (3) 2013)

³ - Source: Research "Vergleich verschiedener Bereifungskonzepte bei schwerer Zugarbeit" (Prof. Yves Reckleben and Sven Jensen, FH-Kiel / University of Applied Sciences Kiel). Tests were performed on dry soil.

² - Nokian Tyres' winter outdoor tests in the Nokian White Hell test center

TECHNICAL SPECIFICATIONS

Nokian TRI 2

SIZE	LI/SS	RIM	PERMITTED RIMS	WIDTH		DIAMETER		LOADED STATIC RADIUS		ROLLING CIRCUMFERENCE		MAXIMUM INFLATION PRESSURE		LOAD CAPACITY				PRODUCT CODE
				mm	in	mm	in	mm	in	mm	in	kPa	psi	40 km/h	25 mph	65 km/h	40 mph	
85-SERIES																		
320/85R28	136 D	DW10	W9, W10, DW11	319	12.6	1 250	49.2	574	22.6	3 782	148.9	320	46	2 575	5 675	2 240	4 940	T445579
80-SERIES																		
250/80R16*	119 G	W8	W7, 7J, 7.5J, 8J, 8.5J, W9, 9, 9.00, 9J	268	10.6	814	32.0	383	15.1	2 488	98.0	450	65	1 750	3 860	1 550	3 415	T845495
340/80R18	138 D	11	W10, W11, 12, W12	343	13.5	1 001	39.4	453	17.8	3 010	118.5	400	58	2 725	6 010	2 360	5 205	T445391
360/80R20	143 D	11	W10, W11, 12, W12	357	14.1	1 092	43.0	495	19.5	3 280	129.1	400	58	3 075	6 780	2 725	6 010	T445389
300/80R24	128 D	DW10	W9, W10, W11, DW11	295	11.6	1 090	42.9	499	19.6	3 292	129.6	320	46	2 060	4 540	1 800	3 970	T445419
340/80R24	135 D	DW11	W10, W11, W12, DW10, DW12	343	13.5	1 154	45.4	532	20.9	3 487	137.3	320	46	2 500	5 510	2 180	4 805	T445376
360/80R24	138 D	DW11	W10, W11, W12, W13, DW10, DW12, DW13	357	14.1	1 186	46.7	542	21.3	3 581	141.0	320	46	2 725	6 010	2 360	5 205	T445378
400/80R24	144 D	DW13	W12, W13, W14L, DW12, DW14L	404	15.9	1 250	49.2	568	22.4	3 764	148.2	320	46	3 250	7 165	2 800	6 175	T445372
440/80R24	149 D	DW14L	W15L, DW15L	441	17.4	1 314	51.7	596	23.5	3 965	156.1	320	46	3 750	8 265	3 250	7 165	T445385
360/80R28	142 D	DW11	W11, W12, W13, DW12, DW13	357	14.1	1 302	51.3	595	23.4	3 946	155.4	320	46	3 000	6 615	2 650	5 840	T445550
400/80R28	146 D	DW13	W12, W13, W14L, DW12, DW14L	404	15.9	1 351	53.2	620	24.4	4 090	161.0	320	46	3 450	7 605	3 000	6 615	T445383
440/80R28	151 D	DW14L	W15L, W16L, DW15L, DW16L	441	17.4	1 415	55.7	644	25.4	4 266	168.0	320	46	4 000	8 820	3 450	7 605	T445337
440/80R30	153 D	DW14L	DW15L, W16L	441	17.4	1 466	57.7	670	26.4	4 430	174.4	320	46	4 125	9 095	3 650	8 045	T445384
480/80R30	157 D	DW15L	DW16L, DW18L	479	18.9	1 530	60.2	694	27.3	4 631	182.3	320	46	4 750	10 470	4 125	9 095	T445386
440/80R34	155 D	DW14L	DW15L, DW16L	441	17.4	1 568	61.7	717	28.2	4 750	187.0	320	46	4 375	9 645	3 875	8 545	T445369
480/80R34	159 D	DW15L	DW16L, DW18L	479	18.9	1 632	64.3	743	29.3	4 939	194.4	320	46	5 000	11 025	4 375	9 645	T445370
480/80R38	161 D	DW15L	DW16L, DW18L	479	18.9	1 733	68.2	793	31.2	5 265	207.3	320	46	5 300	11 685	4 625	10 195	T445377
540/80R38	167 D	DW18L	DW16L	550	21.7	1 829	72.0	834	32.8	5 529	217.7	320	46	6 300	13 890	5 450	12 015	T445338
620/80R42	177 D	DW20B	TW20B, DW21B, TW21B, DW23B, TW23B	625	24.6	2 059	81.1	934	36.8	6 262	246.5	320	46	8 250	18 190	7 300	16 095	T445518
75-SERIES																		
250/75R16*	120 G	W8	W7, 7J, 7.5J, 8J, 8.5J, W9, 9, 9.00, 9J	258	10.2	782	30.8	363	14.3	2 390	94.1	450	65	1 650	3 640	1 450	3 195	T845539
70-SERIES																		
360/70R20	131 D	W11	W10, W12	357	14.1	1 028	40.5	469	18.5	3 104	122.2	320	46	2 240	4 940	1 950	4 300	T445569
500/70R24* (19.5LR24)	159 D	DW16L	DW15L, DW18L	503	19.8	1 310	51.6	585	23.0	3 958	155.8	400	58	5 000	11 025	4 375	9 645	T445467
600/70R30	166 D	DW18L	DW20B									320	46	6 150	13 600	5 300	11 700	T445657
710/70R42	180 D		DW23B									320	46	9 250	20 400	8 000	17 600	T445655
65-SERIES																		
420/65R24	146 D	DW13	W12, W13, W14L, DW12, DW14L, DW15L	418	16.5	1 156	45.5	525	20.7	3 493	137.5	400	58	3 450	7 605	3 000	6 615	T445392
460/65R24	151 D	DW14L	W15L, W16L, DW15L, DW16L	454	17.9	1 208	47.6	550	21.7	3 638	143.2	400	58	4 000	8 820	3 450	7 605	T445393
540/65R24	154 D	DW18L	DW16L	550	21.7	1 312	51.7	587	23.1	3 952	155.6	320	46	4 250	9 370	3 750	8 265	T445420
480/65R28	149 D	DW15L	DW14L, DW16L	479	18.9	1 335	52.6	604	23.8	4 040	159.1	320	46	3 750	8 265	3 250	7 165	T445444
540/65R28	155 D	DW18L	DW16L	550	21.7	1 413	55.6	641	25.2	4 273	168.2	320	46	4 500	9 920	3 875	8 545	T445442
540/65R30	156 D	DW18L	DW16L	550	21.7	1 464	57.6	667	26.3	4 417	173.9	320	46	4 625	10 195	4 000	8 820	T445371
600/65R34	164 D	DW18L	DW20B									320	46	5 800	12 800	5 000	11 000	T445656
600/65R38	166 D	DW18L	DW20B	591	23.3	1 745	68.7	790	31.1	5 290	208.3	320	46	6 000	13 230	5 300	11 685	T445445
650/65R38	170 D	DW20B	DW18L, DW23B	645	25.4	1 811	71.3	819	32.2	5 510	216.9	320	46	6 900	15 210	6 000	13 230	T445443
650/65R42	171 D	DW20A	DW18L, DW23A	645	25.4	1 913	75.3	873	34.4	5 799	228.3	320	46	7 100	15 655	6 150	13 560	T445390

* SB = STEEL BELTED

Read more

[NOKIANTYRES.COM/HEAVY](https://www.nokiantyres.com/heavy)