


nokian[®]
TYRES

NOKIAN TRACTOR KING



REVOLUTIONARY FROM SURFACE TO CORE

Nokian Tractor King is a no-compromise tractor tyre for the heaviest of machinery and the most difficult terrain in forestry, earthmoving and road construction. The design from all-new tread pattern to fortified carcass is nothing short of revolutionary in a tractor tyre.



DURABILITY

Core and sidewall designed for top-class puncture-resistance in toughest conditions.

TRACTION

Wide tread and radically increased amount of tractive edges for grip on all terrains.

TAKES HEAVY LOADS

Innovatively wear-resistant tread design for comfortable, economical kilometres.

HIGH LOAD CAPACITY

Up to 320 kPa

50 % MORE TRACTIVE EDGES

Compared to conventional lug pattern

HIGH SPEED CATEGORY

65 km/h (D)



RADIAL



TUBELESS



STEEL BELTED



CCR



ARAMID SIDEWALLS



PUNCTURE PROTECTION



CHAIN USE



STUDDABLE



STONE EJECTORS



“Top-class traction and lateral grip – even on slippery rocks”

CHRISTOF WIEDERSTEIN
Hergenroth / Germany

TECHNICAL SPECIFICATIONS

Size	LI / SS	Recommended rim	Permitted rims	Width		Diameter		SRI	Inflation pressure for load capacity calculation		Load Capacity kg/lbs												Max. Inflation pressure		Product code	Available
				mm	in	mm	in		kPa	psi	65 km/h	40 mph	50 km/h	30 mph	40 km/h	25 mph	30 km/h	20 mph	20 km/h	10 mph	10 km/h	5 mph	kPa	p.s.i		
500/65R28	150 D	DW16L	DW15L, TW15L, TW16L, DW18L, TW18L	503	19,8	1361	53,6	650	320	46	3350	7385	3520	7760	3670	8090	3850	8490	4120	9085	5030	11090	400	58	T445673	6/2019
540/65R28	154 D	DW18L	DW16L, TW16L, TW18L	550	21,7	1413	55,6	675	320	46	3750	8265	3940	8685	4110	9060	4310	9500	4610	10165	5630	12410	400	58	T445674	11/2018
600/60R28	157 D	DW18L	TW18L, DW20B, TW20B	601	23,7	1431	56,3	675	320	46	4125	9095	4330	9545	4520	9965	4740	10450	5070	11175	6190	13645	400	58	T445675	6/2019
540/65R30	155 D	DW18L	DW16L, TW16L, TW18L	550	21,7	1464	57,6	700	320	46	3875	8545	4070	8975	4240	9350	4460	9835	4770	10515	5810	12810	400	58	T445676	6/2019
540/70R30	159 D	DW18L	DW16L, TW16L, TW18L	540	21,3	1518	59,8	725	320	46	4375	9645	4590	10120	4790	10560	5030	11090	5380	11860	6560	14460	400	58	T445677	11/2018
600/70R30	165 D	DW18L	TW18L, DW20B, TW20B	591	23,3	1602	63,1	750	320	46	5150	11355	5410	11925	5640	12435	5920	13050	6330	13955	7730	17040	400	58	T445678	6/2019
620/75R30	169 D	DW20B	TW20B	625	24,6	1692	66,6	800	320	46	5800	12785	6090	13425	6350	14000	6670	14705	7130	15720	8700	19180	400	58	T445679	6/2019
600/65R34	163 D	DW18L	TW18L, DW20B, TW20B	591	23,3	1644	64,7	775	320	46	4875	10745	5120	11290	5340	11775	5610	12370	6000	13230	7310	16115	400	58	T445680	11/2018
600/70R34	167 D	DW18L	TW18L, DW20B, TW20B	591	23,3	1704	67,1	800	320	46	5450	12015	5720	12610	5970	13160	6270	13825	6700	14770	8180	18035	400	58	T445681	11/2018
600/65R38	165 D	DW18L	TW18L, DW20B, TW20B	591	23,3	1745	68,7	825	320	46	5150	11355	5410	11925	5640	12435	5920	13050	6330	13955	7730	17040	400	58	T445682	6/2019
650/65R38	169 D	DW20B	TW20B	645	25,4	1811	71,3	875	320	46	5800	12785	6090	13425	6350	14000	6670	14705	7130	15720	8700	19180	400	58	T445683	11/2018
650/75R38	175 D	DW20B	TW20B, DW21B, TW21B, DW23B, TW23B	645	25,4	1941	76,4	925	320	46	6900	15210	7250	15985	7560	16665	7940	17505	8490	18715	10350	22820	400	58	T445684	11/2018
650/85R38	178 D	DW20B	TW20B, DW21B, TW21B, DW23B, TW23B	645	25,4	2071	81,5	975	320	46	7500	16535	7880	17370	8210	18100	8630	19025	9230	20350	11250	24800	400	58	T445685	6/2019
710/70R42	179 D	DW23B	TW23B, DW25B, TW25B	716	28,2	2061	81,1	975	320	46	7750	17085	8140	17945	8490	18715	8910	19645	9530	21010	11630	25640	400	58	T445686	6/2019
710/75R42	181 D	DW23B	TW23B, DW25B, TW25B	716	28,2	2133	84	1025	320	46	8250	18190	8660	19090	9030	19910	9490	20920	10150	22375	12380	27295	400	58	T445687	11/2018

In forestry or heavy road use add 40 kPa / 6 psi