

## Nokian Hakkapeliitta Truck

### Nokian Hakkapeliitta Truck F

Sizes  
 295/80 R 22.5  
 315/70 R 22.5  
 315/80 R 22.5  
 385/65 R 22.5

Application  
 Winter steer tyre

- Especially for long and medium haul on trucks and busses
- Autumn fitting recommended



#### Maximum load capacities per axle

Size	Pattern	LI/SS	Inflation Pressure	Single Load	Dual Load
295/80R22.5	Truck F	152/148M	8,50 bar	7100 kg @ 130 km/h	12600 kg @ 130 km/h
315/70R22.5	Truck F	152/148M	8,50 bar	7100 kg @ 130 km/h	12600 kg @ 130 km/h
		154/150L	9,00 bar	7500 kg @ 120 km/h	13400 kg @ 120 km/h
315/80R22.5	Truck F	154/150M	8,25 bar	7500 kg @ 130 km/h	13400 kg @ 130 km/h
		156/150L	8,50 bar	8000 kg @ 120 km/h	13400 kg @ 120 km/h
385/65R22.5	Truck F	158L	8,50 bar	8500 kg @ 120 km/h	-
		160K	9,00 bar	9000 kg @ 110 km/h	-

#### Tyre dimensions

Tyre Size	Pattern Design	Tread depth (mm)	Approved Rims (in)	Overall Diameter (mm)	Tyre Width (mm)	Static Loaded Radius (mm)	Rolling Circ. (mm)	Minimum Dual Spacing (mm)
295/80R22.5	Truck F	16,5	<b>9.00</b> , 8.25	1049	299	489	3189	335
315/70R22.5	Truck F	16	<b>9.00</b> , 8.25	1024	314	472	3109	335
315/80R22.5	Truck F	16,5	<b>9.00</b> , 9.75	1081	314	503	3292	351
385/65R22.5	Truck F	16,5	<b>11.75</b> , 12.25	1088	375	504	3313	-

Compound  
 Special compound for winter steer axle use

#### Properties

- Sharp-edged tread pattern ensures absolute grip and good driving properties
- Good mileage and even wear
- Low rolling resistance and noise level
- SPIRAL SIPE SYSTEM
- DSI - Driving Safety Indicator
- WSI - Winter Safety Indicator
- Stone ejectors
- Stud arrangement marked on shoulders



## Nokian Hakkapeliitta Truck F

### Certificates

- E9 00 2045 (295/80 R 22.5)
- E9 00 2056 (315/70 R 22.5)
- E9 00 2053 (315/80 R 22.5)
- E9 00 2044 (385/65 R 22.5)
- E4-0019977-s (Noise homologation)

29.11.2011