

**Nokian NTR**

**Nokian NTR 68**

Sizes 13 R 22.5  
315/80 R 22.5

Application All-season on/off drive axle tyre  

- For severe conditions



Maximum load capacities per axle

Size	Pattern Design	LI/SS	Inflation Pressure	Single Load	Dual Load
13R22.5	NTR 68	154/150K	8,0 bar	7500 kg @ 110 km/h	13400 kg @ 110 km/h
		156/150G	8,0 bar	4000 kg @ 90 km/h	13400 kg @ 90 km/h
315/80R22.5	NTR 68	156/150K	8,30 bar	8000 kg @ 110 km/h	13400 kg @ 110 km/h

Tyre dimensions

Size	Pattern Design	Tread depth (mm)	Approved Rims (in)	Overall Diameter (mm)	Tyre Width (mm)	Static Loaded Radius (mm)	Rolling Circ. (mm)	Minimum Dual Spacing (mm)
13R22.5	NTR 68	20,0	<b>9.00</b> , 9.75	1124	328	524,4	3432,5	350
315/80R22.5	NTR 68	20,0	<b>9.00</b> , 9.75	1081	312	497,8	3296,8	351

Compound Special cut and crack resistant compound for All-season use

Properties

- Low heat build-up
- Good self-cleaning and grip due to open pattern design
- M+S marking
- Driving Safety Indicators (DSI)

Certificates

- E4-54R-0018792 (13 R 22.5)
- E4-54R-0018793 (315/80 R 22.5)
- E7-117R-010906-S (Noise homologation)

17.6.2009