

Nokian Noktop Pro

Nokian Noktop 63

| | |
|---------------|---|
| Width | 205, 220, 230, 240, 255 mm |
| Length | 2780 - 3365 mm |
| Pattern depth | 13,5 mm |
| Application | Multipurpose tread for All season use <ul style="list-style-type: none"> • Free rolling axles • Especially for low profile casings • Also for off-road service |



Technical data

| Order code | Width mm | Length mm | Pattern Depth mm | Kg/m | Kg/pcs | Product code |
|--------------|----------|-----------|------------------|------|--------|----------------|
| 63 205 | 205 | 3365 | 13,5 | 3,2 | 10,7 | T672411 |
| 63 220 | 220 | 3270 | 13,5 | 3,7 | 12,1 | T672412 |
| 63 230 | 230 | 3270 | 13,5 | 3,9 | 12,7 | T672413 |
| 63 240 | 240 | 3350 | 13,5 | 4,1 | 13,9 | T672414 |
| 63 255 | 255 | 3350 | 13,5 | 4,5 | 15,1 | T672415 |
| 63 205 Short | 205 | 2885 | 13,5 | 3,2 | 9,2 | T672421 |
| 63 220 Short | 220 | 2880 | 13,5 | 3,5 | 10,2 | T672422 |
| 63 230 Short | 230 | 3000 | 13,5 | 4,0 | 12,1 | T672423 |
| 63 240 Short | 240 | 2950 | 13,5 | 4,1 | 12,2 | T672424 |

| | |
|--------------|---|
| Compound | Special rubber compound for free-rolling use <ul style="list-style-type: none"> • Excellent mileage |
| Green | <ul style="list-style-type: none"> • HA-oil free • Low rolling resistance • Excellent durability • Production process fulfils environmental standards of ISO 14 001 |
| Properties | <ul style="list-style-type: none"> • Low heat generation • Uniform shoulder construction • Good lateral grip and precise handling |
| Other | <ul style="list-style-type: none"> • Economical for retreaders • Low weight/meter (kg/m) • Also short versions available |
| Other | M+S – marking |
| Alternatives | Noktop 32, Noktop 72 |

25.6.2009